

Condulet® Conduit Bodies With Covers

OE Series

Cl. I, Div. 1 & 2, Groups C, D
Cl. II, Div. 1, Groups E, F, G
Cl. II, Div. 2, Groups F, G
Cl. III
NEMA 7CD, 9EFG

Explosionproof
Dust-Ignitionproof

3F

3F

Applications:

OE series are installed in conduit systems within hazardous areas to:

- Protect conductors in threaded rigid conduit
- Act as pulling and splice fittings
- Interconnect lengths of conduit
- Change direction of conduit
- Provide access for maintenance and future system changes

Features:

OE conduit outlet bodies have:

- Taper threaded hubs for ground continuity
- Smooth integral hub bushings to protect conductor insulation when pulling
- Five different hub arrangements
- Accurately machined body with blind tapped screw holes
- Most compact design of all hazardous area outlet bodies

Certifications and Compliances:

- NEC/CEC:
 - Class I, Division 1 & 2, Groups C, D
 - Class II, Division 1, Groups E, F, G
 - Class II, Division 2, Groups F, G
 - Class III
- UL Standard: 1203
- CSA Standard: C22.2 No. 30

Standard Materials:

- Feraloy® iron alloy (1/2" and 3/4" fittings)
- Copper-free aluminum (1" fittings)

Standard Finishes:

- Electrogalvanized and aluminum acrylic paint

Options:

Description

Corro-free™ epoxy powder coat

Suffix

S752

Size Ranges:

- Hub - 1/2" to 1"

OEC



Hub Size	Cat. #
1/2	OEC1
3/4	OEC2
1	OEC3 SA

OET



Hub Size	Cat. #
1/2	OET1
3/4	OET2
1	OET3 SA

OELL



Hub Size	Cat. #
1/2	OELL1
3/4	OELL2
1	OELL3 SA

OELB




Hub Size	Cat. #
1/2	OELB1
3/4	OELB2
1	OELB3 SA

OELR



Hub Size	Cat. #
1/2	OELR1
3/4	OELR2
1	OELR3 SA

Dimensions In Inches:



Hub Size in.	a	b	c	d	e	f
1/2	4 1/8	1 9/16	1 13/16	1 1/16	7/8	5/8
3/4	4 5/16	1 7/8	2 1/16	1 1/16	7/8	3/4
1	5 1/16	2 3/8	2 5/16	3/4	1 1/16	7/8

Crouse-Hinds

by E.T.N

www.crouse-hinds.com US: 1-866-764-5454 CAN: 1-800-265-0502 Copyright© 2014 Eaton's Crouse-Hinds Business

Condulet® Conduit Bodies With Covers

OE Series

Cl. I, Div. 1 & 2, Groups C, D
Cl. II, Div. 1, Groups E, F, G
Cl. II, Div. 2, Groups F, G
Cl. III
NEMA 7CD, 9EFG

Explosionproof
Dust-Ignitionproof

3F

3F

Applications:

OE series are installed in conduit systems within hazardous areas to:

- Protect conductors in threaded rigid conduit
- Act as pulling and splice fittings
- Interconnect lengths of conduit
- Change direction of conduit
- Provide access for maintenance and future system changes

Features:

OE conduit outlet bodies have:

- Taper threaded hubs for ground continuity
- Smooth integral hub bushings to protect conductor insulation when pulling
- Five different hub arrangements
- Accurately machined body with blind tapped screw holes
- Most compact design of all hazardous area outlet bodies

Certifications and Compliances:

- NEC/CEC:
 - Class I, Division 1 & 2, Groups C, D
 - Class II, Division 1, Groups E, F, G
 - Class II, Division 2, Groups F, G
 - Class III
- UL Standard: 1203
- CSA Standard: C22.2 No. 30

Standard Materials:

- Feraloy® iron alloy ($\frac{1}{2}$ " and $\frac{3}{4}$ " fittings)
- Copper-free aluminum (1" fittings)

Standard Finishes:

- Electrogalvanized and aluminum acrylic paint

Options:

Description

Corro-free™ epoxy powder coat

Suffix

S752

Size Ranges:

- Hub - $\frac{1}{2}$ " to 1"

OEC



Hub Size	Cat. #
$\frac{1}{2}$	OEC1
$\frac{3}{4}$	OEC2
1	OEC3 SA

OET



Hub Size	Cat. #
$\frac{1}{2}$	OET1
$\frac{3}{4}$	OET2
1	OET3 SA

OELL



Hub Size	Cat. #
$\frac{1}{2}$	OELL1
$\frac{3}{4}$	OELL2
1	OELL3 SA

OELB




Hub Size	Cat. #
$\frac{1}{2}$	OELB1
$\frac{3}{4}$	OELB2
1	OELB3 SA

OELR



Hub Size	Cat. #
$\frac{1}{2}$	OELR1
$\frac{3}{4}$	OELR2
1	OELR3 SA

Dimensions In Inches:



Hub Size in.	a	b	c	d	e	f
$\frac{1}{2}$	$4\frac{1}{8}$	$1\frac{9}{16}$	$1\frac{13}{16}$	$1\frac{1}{16}$	$\frac{7}{8}$	$\frac{5}{8}$
$\frac{3}{4}$	$4\frac{5}{16}$	$1\frac{7}{8}$	$2\frac{1}{16}$	$1\frac{1}{16}$	$\frac{7}{8}$	$\frac{3}{4}$
1	$5\frac{1}{16}$	$2\frac{3}{8}$	$2\frac{5}{16}$	$\frac{3}{4}$	$1\frac{1}{16}$	$\frac{7}{8}$

Crouse-Hinds

by E.T.N

www.crouse-hinds.com US: 1-866-764-5454 CAN: 1-800-265-0502 Copyright© 2014 Eaton's Crouse-Hinds Business