

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



1010ENK Wway 10X10 NK PNTD WW End Cooper B-Line/Cable Tray

Catalog Number	1010ENK
Manufacturer	Cooper B-Line/Cable Tray
Description	Eaton B-Line Series Wireway End, No Knockout, Wireway End,
	Nema 1, Steel, Ansi 61 Gray Painted Finish, 10" X 10"
Weight per unit	2.2 (lbs/each)
Product Category	Nema Type 1 Wireway & Fittings

Features

Cover Type	SCREW
dimensions	10.0600 IN X 10.0000 IN X 10.0000 IN
Material	Steel

Material, Color, and Finish

Finish	PLAIN (NO FINISH)

Dimensions and Weight

Height	10.00 ln
Width	10.00 ln

Descriptions

Description	WWAY 10X10 NK PNTD WW END
extra long description	B-LINE 1010 E NK SC WIREWAY END W/O
Features	Eaton's B-Line series wiring troughs provide reliable environmental protection and are used to house runs of control and power cable in wiring, junction, pull, and termination applications.
Long Description	Eaton B-Line series wireway end, No knockout, Wireway end, NEMA 1, Steel, ANSI 61 gray painted finish, 10" X 10"
Product Type	SC Wireway End W/O Ko 10X10

Manufacturer Information

Brand	Eaton
GTIN	00782051108729
Manufacturers Part Number	1010 E NK
UPC	782051108729

Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Туре	Wireway end

Packaging

Carton	1	
Weight Per each	2.198	

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

	and and
Application	Ind Facilities & Factories - Facility: Power Distribution and ControlCommercial / Institutional Buildings / Structures - Safety and Security SystemsInd Facilities & Factories - Facility: Critical PowerCommercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - OtherInd Facilities & Factories - Industrial Facilities/Factories - OtherInd Facilities & Factories - Facility: Safety and Security SystemsI
Enclosure	NEMA 1, IP30
standard	UL Listed, CSA C22.2., NEMA