


Range & dryer power receptacles


Product description

3-pole, 3-wire non-grounding
30A, 125/250V/AC
50A, 125/250V/AC



Design features

- For replacement use in older homes with 3-wire range and dryer connection points
- Heavy gauge galvanized steel mounting strap for corrosion resistance
- Flush receptacles fit one-gang or two-gang enclosures
- For use with copper or aluminum wire
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom



32B



112



1258

Flush power receptacles

Rating		NEMA	Description	Color	Catalog no.		
A	V/AC						
30	125/250	10-30R	Flush mount dryer power receptacle, matching plug S80	B	□ 38B	•	•
50	125/250	10-50R	Flush mount range power receptacle, matching plug S80	B	□ 32B	•	•

Listed to UL498 & UL943, file no. E60120; NOM certified

Surface power receptacles

Rating		NEMA	Description	Color	Catalog no.		
A	V/AC						
30	125/250	10-30R	Flush mount dryer power receptacle, matching plug S80	BK	□ 125	•	•
50	125/250	10-50R	Flush mount range power receptacle, matching plug S80	BK	□ 112	•	•

Listed to UL498, file no. E15058; NOM certified

Flush power receptacles

Rating		NEMA	Description	Color	Catalog no.		
A	V/AC						
30	125/250	14-30R	Flush mount dryer power receptacle, matching plug S21	BK	□ 1257	•	•
50	125/250	14-50R	Flush mount range power, matching plug S21	BK	□ 1258	•	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Color ordering information:

B (Brown), BK (Black)

B	BK
(Brown)	(Black)

Dimensional information: B-70 **Specification information:** Please visit www.eaton.com/wiringdevices

Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page G-21

 RoHS compliant - Page G-21

Range & dryer power receptacles

Product description

3-pole, 3-wire non-grounding
30A, 125/250V/AC
50A, 125/250V/AC



10-30R




10-50R



14-30R



14-50R



32B



112



1258

Design features

- For replacement use in older homes with 3-wire range and dryer connection points
- Heavy gauge galvanized steel mounting strap for corrosion resistance
- Flush receptacles fit one-gang or two-gang enclosures
- For use with copper or aluminum wire
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

Flush power receptacles

Rating		NEMA	Description	Color	Catalog no.		
A	V/AC						
30	125/250	10-30R	Flush mount dryer power receptacle, matching plug S80	B	□ 38B	•	•
50	125/250	10-50R	Flush mount range power receptacle, matching plug S80	B	□ 32B	•	•

Listed to UL498 & UL943, file no. E60120; NOM certified

Surface power receptacles

Rating		NEMA	Description	Color	Catalog no.		
A	V/AC						
30	125/250	10-30R	Flush mount dryer power receptacle, matching plug S80	BK	□ 125	•	•
50	125/250	10-50R	Flush mount range power receptacle, matching plug S80	BK	□ 112	•	•

Listed to UL498, file no. E15058; NOM certified

Flush power receptacles

Rating		NEMA	Description	Color	Catalog no.		
A	V/AC						
30	125/250	14-30R	Flush mount dryer power receptacle, matching plug S21	BK	□ 1257	•	•
50	125/250	14-50R	Flush mount range power, matching plug S21	BK	□ 1258	•	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Color ordering information:

B (Brown), BK (Black)

B

(Brown)

BK

(Black)

Dimensional information: B-70 **Specification information:** Please visit www.eaton.com/wiringdevices

Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page G-21



RoHS compliant - Page G-21