



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



126S 2" Steel Bonding Locknut

Nsi Industries

| | |
|------------------|--------------------------------------|
| Catalog Number | 126S |
| Manufacturer | Nsi Industries |
| Description | Locknut, Bonding, Steel, Size 2 Inch |
| Weight per unit | 0.1140 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|-------------|--|
| Cable Entry | Through the fitting or conduit that the locknut is attached to |
| Material | Steel |
| media | Yes |

Material, Color, and Finish

| | |
|--------|--------------------|
| Finish | Zinc Electroplated |
|--------|--------------------|

Dimensions and Weight

| | |
|------|---|
| Size | 2 |
|------|---|

Descriptions

| | |
|------------------------|---|
| Description | 2" STEEL BONDING LOCKNUT |
| extra long description | BPT 126-S 2 IN Steel Grounding Lock |
| Long Description | Locknut, Bonding, Steel, Size 2 Inch |
| Product Type | 2 In Steel Grounding Locknut, Box Of 10 |
| Special Features | Used in harsh vibration environments |

Manufacturer Information

| | |
|---------------------------|---------------------|
| Brand | Bridgeport Fittings |
| GTIN | 00781747201263 |
| Manufacturers Part Number | 126-S |
| UPC | 781747201263 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs |
| Type | Locknuts |

Trade Size

| | |
|------------|---|
| Trade Size | 2 |
|------------|---|

Packaging

| | |
|-----------------|-------|
| Carton | 10 |
| Package | 50 |
| Weight Per each | 0.114 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Used in harsh vibration environments to fasten threaded conduit to unthreaded opening in a box or enclosure.

standard

cULus