



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **130C112X30FT Linerless Rubber Splicing Tape, 1-1/2" X 30', BK** *Minnesota Mining (3M)*

|                  |                                                                                                                                                                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | 130C112X30FT                                                                                                                                                                                                                                                                                                                           |
| Manufacturer     | Minnesota Mining (3M)                                                                                                                                                                                                                                                                                                                  |
| Description      | Scotch® Tape 130C Is A Linerless 30 Mil Thick, Premium Grade, Rubber Splicing Tape Used For Splicing and Terminating Cables and Wires. It Withstands Temperatures Up to 194 °F (90 °C) With Emergency Overload Up to 266 °F (130 °C). The Tape Has Excellent Electrical and Mechanical Properties to Provide Moisture Seal Protection. |
| Weight per unit  | 0.9000 (lbs/each)                                                                                                                                                                                                                                                                                                                      |
| Product Category | Markers & Marking Tapes - Tape                                                                                                                                                                                                                                                                                                         |

### **Descriptions**

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description            | LINERLESS RUBBER SPLICING TAPE,1-1/2" X 30',BLACK                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| extra long description | 3M 7000006086 Scotch® Linerless Rub                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Features               | Scotch® Tape 130C is a highly conformable tape that provides electrical and mechanical protection with the combination of an aggressive rubber resin adhesive and a self fusing, ethylene propylene backing. The tape provides primary insulation for solid, dielectric insulated cables rated through 69 kV. This tape is designed for low and high voltage, bus bar insulation, end sealing of cables and jacket repair applications. It has outstanding mechanical and electrical properties that offer moisture seal and v |
| Long Description       | Scotch® Tape 130C is a linerless 30 mil thick, premium grade, rubber splicing tape used for splicing and terminating cables and wires. It withstands temperatures up to 194 °F (90 °C) with emergency overload up to 266 °F (130 °C). The tape has excellent electrical and mechanical properties to provide moisture seal protection.                                                                                                                                                                                         |
| Product Type           | Scotch® Linerless Rubber Splicing Tape 130C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Special Features       | provides excellent thermal dissipation of splice heat                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### **Manufacturer Information**

|                           |                |
|---------------------------|----------------|
| Brand                     | Scotch         |
| GTIN                      | 00054007417187 |
| Manufacturers Part Number | 7000006086     |
| UPC                       | 054007417187   |

### **Taxonomies, Classifications, and Categories**

|                      |                                     |
|----------------------|-------------------------------------|
| Category Description | TAPE                                |
| Type                 | linerless Ethylene Propylene Rubber |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Availability

|        |          |
|--------|----------|
| Status | Inactive |
|--------|----------|

## Packaging

|        |    |
|--------|----|
| Carton | 12 |
|--------|----|

|                 |     |
|-----------------|-----|
| Weight Per each | 0.9 |
|-----------------|-----|

## Uses, Certifications, and Standards

|             |              |
|-------------|--------------|
| Application | High Voltage |
|-------------|--------------|

|          |                                      |
|----------|--------------------------------------|
| standard | ASTM D-4388 type 1, 2 & 3 HH-I-3825B |
|----------|--------------------------------------|