

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging Carton

Weight Per each

1418N4S16J12 N4X Wallmount Encl W/Panel - 24 X 24 X 12 - 316 SS Hammond MEG

Hammond MFG.	
Catalog Number	1418N4S16J12
Manufacturer	Hammond MFG.
Description	N4X Wallmount Encl W/Panel - 24 X 24 X 12 - 316 SS
Weight per unit	71.0 (lbs/each)
Product Category	Nema Types 4 & 4X Metallic Enc
Features	
Material	Stainless Steel
Material, Color, and Finish	
Color	Unpainted
Dimensions and Weight	
Size	24 in x 24 in x 12 in
Descriptions	
Description	N4X WALLMOUNT ENCL W/PANEL - 24 X 24 X 12 - 316 SS
extra long description	HMND 1418N4S16J12 NEMA 4 316SS ENCL
Long Description	
Product Type	Nema 4 316SS Encl 24X24X12
Special Features	Formed 14 gauge 304 or 316 stainless steel. Smooth, continuously welded seams without knockouts, cutouts or holes. Door stiffeners are provided in the larger enclosures for extra rigidity. Welded brackets provide for enclosure mounting. Formed lip on door and enclosure excludes flowing liquids and contaminants. Stainless steel continuous hinge on door may be removed by pulling the stainless steel hinge pin. Door is secured with easily operated stainless steel clamps. Provision for padlocking. Seaml
Manufacturer Information	
Brand	Hammond MFG.
GTIN	00623980149110
Manufacturers Part Number	1418N4S16J12
UPC	623980149110
Taxonomies, Classifications, and (Categories
Category Description	STEEL JUNCTION BOXES
Туре	Type 4X Stainless Steel Wallmount Enclosure
D 1 1	

1 71



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

cs, oci tilications, and sta	iluaius
Application	Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures. Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem
Mounting	WALL
nema rating	13;3R;4X
standard	CSA, UL, CE