

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2025 North Masch Branch Road Suite 105 76207-0000, TX Denton Phone: 940-381-9070

Fax: 940-380-0325



1418N4SSE8 24X20X8 N4X SS4 CH Clamp CVR Hammond MFG.

Catalog Number 1418N4SSE8 Hammond MFG. Manufacturer N4X Wallmount Encl W/Panel - 24 X 20 X 8 - 304 SS Description 61.0 (lbs/each) Weight per unit Product Category Nema Types 4 & 4X Metallic Enc

Features

Material Stainless Steel

Material, Color, and Finish

Color Unpainted

Dimensions and Weight

Size 24 in x 20 in x 8 in

Descriptions

Description 24X20X8 N4X SS4 CH CLAMP CVR extra long description HMND 1418N4SSE8 NEMA 4X ENCL PANL 2 Long Description N4X WALLMOUNT ENCL W/PANEL - 24 X 20 X 8 - 304 SS **Product Type** Nema 4X Encl Panl 24X20X8 Special Features Formed 14 gauge 304 or 316 stainless steel. Smooth,

continuously welded seams without knockouts, cutouts or holes. Door stiffeners are provided in the larger enclosures for extra rigidity. Welded brackets provide for enclosure mounting. Formed lip on door and enclosure excludes flowing liquids and contaminants. Stainless steel continuous hinge on door may be removed by pulling the stainless steel hinge pin. Door is secured with easily operated stainless steel clamps. Provision for

padlocking. Seaml

Manufacturer Information

Brand Hammond MFG. 00623980384856 **GTIN** Manufacturers Part Number 1418N4SSE8 **UPC** 623980384856

Taxonomies, Classifications, and Categories

Category Description STEEL JUNCTION BOXES Type Type 4X Stainless Steel Wallmount Enclosure

Packaging

Carton 61 Weight Per each



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2025 North Masch Branch Road Suite 105 76207-0000, TX Denton Phone: 940-381-9070 Fax: 940-380-0325

Uses, Certifications, and Standards

es, cei illications, and star	iudi us
Application	Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures. Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem
Mounting	WALL
nema rating	13;3R;4X
standard	CSA, UL, CE