



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



158DC 3" Watertight Hub

Nsi Industries

| | |
|------------------|--|
| Catalog Number | 158DC |
| Manufacturer | Nsi Industries |
| Description | Threaded Hub, Zinc Die Cast, Size 3 Inch |
| Weight per unit | 2.4 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|-------------|--|
| Cable Entry | Through Rigid conduit into throat of fitting |
| Material | Zinc Die Cast |
| media | Yes |

Material, Color, and Finish

| | |
|--------|--------------|
| Finish | Ball burnish |
|--------|--------------|

Dimensions and Weight

| | |
|------|---|
| Size | 3 |
|------|---|

Descriptions

| | |
|------------------------|--|
| Description | 3" WATERTIGHT HUB |
| extra long description | BPT 158-DC 3 IN Threaded Hub, Box o |
| Long Description | Threaded Hub, Zinc Die Cast, Size 3 Inch |
| Product Type | 3 In Threaded Hub, Box Of 5 |
| Special Features | UL Type 4 Water Tight |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Bridgeport |
| GTIN | 00781747091581 |
| Manufacturers Part Number | 158-DC |
| UPC | 781747091581 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR |
| Type | Threaded Hubs |

Trade Size

| | |
|------------|---|
| Trade Size | 3 |
|------------|---|

Packaging

| | |
|-----------------|-----|
| Carton | 5 |
| Weight Per each | 2.4 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

To secure threaded rigid service entrance conduit to box or enclosure. Insulated throat rated 105 degree c. UL listed Type 4 - Watertight. Suitable for Aluminum and Steel Rigid Conduit

standard

UL, CSA

Temperature Rating

105 C