

Rigid/Intermediate Grade Conduit Fittings

Conduit Couplings

THREE-PIECE CONDUIT COUPLINGS – MALLEABLE IRON

Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

Features:

- NPSM threads

Standard Materials:

- Heavy duty casting
- Malleable iron

Standard Finish:

- Zinc plated

Options:

Description

- Hot dip galvanized**Suffix HDG**

Malleable Iron (Concrete Tight)

UL File No. E-19189



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|-------------|--------|-----------|------------------|
| 190M | 1/2" | 25 | 23 |
| 191 | 3/4" | 25 | 35 |
| 192 | 1" | 10 | 60 |
| 193 | 1 1/4" | 5 | 91 |
| 194 | 1 1/2" | 5 | 167 |
| 195 | 2" | 5 | 215 |
| 196 | 2 1/2" | 2 | 430 |
| 197 | 3" | 1 | 463 |
| 198 | 3 1/2" | 1 | 655 |
| 199 | 4" | 1 | 800 |
| 188† | 5" | 1 | 1200 |
| 189† | 6" | 1 | 2100 |

†Not UL Listed.

NO DISASSEMBLY RAIN-TIGHT THREE-PIECE CONDUIT COUPLINGS – STEEL

Applications:

- Used to join two lengths of rigid and IMC conduit together in applications where conduit cannot be turned
- Unique design allows for a quick and easy install which translates into labor savings when compared with traditional fittings

Features:

- Manufactured out of steel to provide mechanical protection and solid grounding of one conduit to another
- Zinc electroplated design which protects against corrosion in damp locations
- No disassembly design which allows for the pairing of two pieces of conduit without the hassle of taking apart the fitting; conduit is input on each end of the coupling and the locknut is tightened down to provide quick and easy raintight seal
- Neoprene rubber o-ring which prevents against the penetration of water or moisture
- RoHS compliant

Standard Materials:

- Body and gland nut – steel
- O-ring – neoprene rubber

Standard Finish:


- Zinc electroplated



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|---------------|--------|-----------|------------------|
| 190RTQ | 1/2" | 125 | 23 |
| 191RTQ | 3/4" | 100 | 29 |
| 192RTQ | 1" | 64 | 48 |
| 193RTQ | 1 1/4" | 48 | 65 |
| 194RTQ | 1 1/2" | 32 | 97 |
| 195RTQ | 2" | 24 | 138 |

Dimensions (in Inches):

| Cat. # | A | B |
|---------------|---------|---------|
| 190RTQ | 1 1/16 | 1 5/8 |
| 191RTQ | 1 11/16 | 1 9/16 |
| 192RTQ | 1 3/4 | 1 15/16 |
| 193RTQ | 1 3/4 | 2 5/16 |
| 194RTQ | 1 13/16 | 2 13/16 |
| 195RTQ | 2 1/16 | 3 5/16 |



Rigid/Intermediate Grade Conduit Fittings

Conduit Couplings

Rigid Fittings

RIGID CONDUIT COUPLINGS – STEEL

Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

Standard Material:

- Galvanized steel

UL File No. E-25501



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| RC50 | 1/2" | 10 | 12 |
| RC75 | 3/4" | 10 | 18 |
| RC100 | 1" | 10 | 29 |
| RC125 | 1 1/2" | 5 | 38 |
| RC150 | 1 1/2" | 5 | 52 |
| RC200 | 2" | 5 | 69 |
| RC250 | 2 1/2" | 2 | 181 |
| RC300 | 3" | 1 | 220 |
| RC350 | 3 1/2" | 1 | 377 |
| RC400 | 4" | 1 | 298 |
| RC500 | 5" | 1 | 477 |
| RC600 | 6" | 1 | 684 |

RIGID CONDUIT COUPLINGS – ALUMINUM

Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

Features:

- Lightweight
- Easy to install
- Corrosion-resistant

Standard Material:

- Aluminum

UL File No. E-324286



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|---------|--------|-----------|------------------|
| RC50SA | 1/2" | 50 | 6 |
| RC75SA | 3/4" | 50 | 9 |
| RC100SA | 1" | 50 | 13 |
| RC125SA | 1 1/4" | 50 | 19 |
| RC150SA | 1 1/2" | 50 | 23 |
| RC200SA | 2" | 20 | 35 |
| RC250SA | 2 1/2" | 12 | 68 |
| RC300SA | 3" | 12 | 91 |
| RC350SA | 3 1/2" | 12 | 108 |
| RC400SA | 4" | 12 | 142 |
| RC500SA | 5" | 1 | 242 |
| RC600SA | 6" | 1 | 320 |

Rigid/Intermediate Grade Conduit Fittings

Conduit Couplings

THREE-PIECE CONDUIT COUPLINGS – MALLEABLE IRON

Applications:

- Used to join two lengths of threaded conduit; couples conduit when conduit cannot be turned

Features:

- NPSM threads

Standard Materials:

- Heavy duty casting
- Malleable iron

Standard Finish:

- Zinc plated

Options:

Description

- Hot dip galvanized**Suffix** **HDG**

Malleable Iron (Concrete Tight)

UL File No. E-19189



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|-------------|--------|-----------|------------------|
| 190M | 1/2" | 25 | 23 |
| 191 | 3/4" | 25 | 35 |
| 192 | 1" | 10 | 60 |
| 193 | 1 1/4" | 5 | 91 |
| 194 | 1 1/2" | 5 | 167 |
| 195 | 2" | 5 | 215 |
| 196 | 2 1/2" | 2 | 430 |
| 197 | 3" | 1 | 463 |
| 198 | 3 1/2" | 1 | 655 |
| 199 | 4" | 1 | 800 |
| 188† | 5" | 1 | 1200 |
| 189† | 6" | 1 | 2100 |

†Not UL Listed.

NO DISASSEMBLY RAIN-TIGHT THREE-PIECE CONDUIT COUPLINGS – STEEL

Applications:

- Used to join two lengths of rigid and IMC conduit together in applications where conduit cannot be turned
- Unique design allows for a quick and easy install which translates into labor savings when compared with traditional fittings

Features:

- Manufactured out of steel to provide mechanical protection and solid grounding of one conduit to another
- Zinc electroplated design which protects against corrosion in damp locations
- No disassembly design which allows for the pairing of two pieces of conduit without the hassle of taking apart the fitting; conduit is input on each end of the coupling and the locknut is tightened down to provide quick and easy raintight seal
- Neoprene rubber o-ring which prevents against the penetration of water or moisture
- RoHS compliant

Standard Materials:

- Body and gland nut – steel
- O-ring – neoprene rubber

Standard Finish:


- Zinc electroplated



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|---------------|--------|-----------|------------------|
| 190RTQ | 1/2" | 125 | 23 |
| 191RTQ | 3/4" | 100 | 29 |
| 192RTQ | 1" | 64 | 48 |
| 193RTQ | 1 1/4" | 48 | 65 |
| 194RTQ | 1 1/2" | 32 | 97 |
| 195RTQ | 2" | 24 | 138 |

Dimensions (in Inches):

| Cat. # | A | B |
|---------------|---------|---------|
| 190RTQ | 1 1/16 | 1 5/8 |
| 191RTQ | 1 11/16 | 1 9/16 |
| 192RTQ | 1 3/4 | 1 15/16 |
| 193RTQ | 1 3/4 | 2 5/16 |
| 194RTQ | 1 13/16 | 2 13/16 |
| 195RTQ | 2 1/16 | 3 5/16 |



Rigid/Intermediate Grade Conduit Fittings

Conduit Couplings

Rigid Fittings

RIGID CONDUIT COUPLINGS – STEEL

Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

Standard Material:

- Galvanized steel

UL File No. E-25501



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| RC50 | 1/2" | 10 | 12 |
| RC75 | 3/4" | 10 | 18 |
| RC100 | 1" | 10 | 29 |
| RC125 | 1 1/2" | 5 | 38 |
| RC150 | 1 1/2" | 5 | 52 |
| RC200 | 2" | 5 | 69 |
| RC250 | 2 1/2" | 2 | 181 |
| RC300 | 3" | 1 | 220 |
| RC350 | 3 1/2" | 1 | 377 |
| RC400 | 4" | 1 | 298 |
| RC500 | 5" | 1 | 477 |
| RC600 | 6" | 1 | 684 |

RIGID CONDUIT COUPLINGS – ALUMINUM

Applications:

- Used to join two lengths of threaded rigid or IMC conduit; can be used in both indoor and outdoor applications

Features:

- Lightweight
- Easy to install
- Corrosion-resistant

Standard Material:

- Aluminum

UL File No. E-324286



| Cat. # | Size | Unit Qty. | Wt. Lbs. Per 100 |
|---------|--------|-----------|------------------|
| RC50SA | 1/2" | 50 | 6 |
| RC75SA | 3/4" | 50 | 9 |
| RC100SA | 1" | 50 | 13 |
| RC125SA | 1 1/4" | 50 | 19 |
| RC150SA | 1 1/2" | 50 | 23 |
| RC200SA | 2" | 20 | 35 |
| RC250SA | 2 1/2" | 12 | 68 |
| RC300SA | 3" | 12 | 91 |
| RC350SA | 3 1/2" | 12 | 108 |
| RC400SA | 4" | 12 | 142 |
| RC500SA | 5" | 1 | 242 |
| RC600SA | 6" | 1 | 320 |