

# 2001 SERIES

## 1/2" CONDUIT MOUNTING

### 180° SWIVEL, LEXAN® HOUSING

### PHOTOCONTROL



## APPLICATIONS

- Flood lamp
- Patio lamp
- Decorative lighting

## FEATURES

**SENSOR:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.

**OPERATION:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.

**STANDARDS:** Meets ANSI/UL773A.

**HOUSING:** All Lexan® enclosures are impact and vandal resistant. Translucent Lexan® Dome prolongs cell life by further screening out ultraviolet rays. Dome and base are ultrasonically welded for maximum strength.

**ENERGY SAVINGS:**

Works with screw base CFLs.

## SPECIFICATIONS

**ON/OFF:** Turn ON is 1 to 5fc. Turn OFF is 3 to 15fc, without the slide in position. ON/OFF adjustment is easily made by moving a slide cover. No tools required.

**TIME DELAY:** ON and OFF.

**CELL:** Cadmium sulphide, epoxy conformal coated 1/2" diameter.

**CONTACTS:** Remain closed between dusk and dawn. (The unit fails in the ON position).

**LEAD WIRES:** Three color coded, minimum 6" wire leads, #16AWG, rated for 105 °C.

**POWER CONSUMPTION:**

Averages under 1 watt.

**TEMPERATURE RANGE:**

-40 °F to +140 °F (-40 °C to +60 °C).

**FAIL MODE:** ON.

**WARRANTY:** 5 years.

CAT. NO.	UPC CODE	VOLTAGE (VAC) 50-60Hz	RATING		LED
			TUNGSTEN	BALLAST	
2001	60015	120	2000W	1800VA	600VA
2002	60016	208-277	3470-4620W	2080-2770VA	1040-1385VA
<b>NEW!</b> 2006*	60028	347	5760W	3470VA	-
2018**	62021	480	7500W	4800VA	-
73866	62020	Mounting Bracket	-	-	-

\*CSA certified only. \*\*Not UL or CSA rated.

