



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

132 Professional Dr.
72023-0000, AR Cabot
Phone: 501-605-1780
Fax: 501-605-1785



24FP4740C 40W 2X4 Led Flat Panel 40K

Cooper Lighting Solutions

| | |
|------------------|---|
| Catalog Number | 24FP4740C |
| Manufacturer | Cooper Lighting Solutions |
| Description | 2X4 Led Recessed Flat Panel, 4700 Lumen, 4000K, 80 Cri, 0-10V Continuous Dimming Driver |
| Weight per unit | 25.8 (lbs/each) |
| Product Category | Led Recessed Architectural & S |

Features

| | |
|-----------------|---|
| amperage rating | 0.15@277V A |
| Ballast Type | N/A IN |
| Lamp Type | INCANDESCENT LANDSCAPE LIGHT FIXTURE, ECLIPSE TYPE; ALUMINUM MATERIAL; 4.5 INCH W X 18.5 INCH H SIZE; TEXTURED ARCHITECTURAL BRONZE FINISH; UL (CANADA AND US), CSA, ETL (US) APPROVAL; 8 INCH IN-GROUND STAKE, 18 INCH STEM MOUNTING |
| Voltage Rating | 120/277 VAC |
| Wattage | 40.3W |

Dimensions and Weight

| | |
|--------|-----------|
| Height | 50.438 in |
| Length | 50.813 in |
| Width | 3.125 in |

Descriptions

| | |
|------------------------|---|
| Description | 40W 2X4 LED FLAT PANEL 40K |
| extra long description | ETNCL 24FP4740C 2X4 FANEL 4700L, 4 |
| Long Description | 2x4 LED recessed flat panel, 4700 Lumen, 4000K, 80 CRI, 0-10V continuous dimming driver |
| Product Type | 2X4 Fpanel 4700L, 40K, 0-10V |
| Special Features | Ultra thin less than 2" height fits shallow plenums with room to spare |

Manufacturer Information

| | |
|---------------------------|-------------------------|
| Brand | METALUX COMMERCIAL |
| GTIN | 00080083801480 |
| Manufacturers Part Number | 24FP4740C |
| sub brand | Fpanel LED Panel Series |
| UPC | 080083801480 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

132 Professional Dr.
72023-0000, AR Cabot
Phone: 501-605-1780
Fax: 501-605-1785

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | LED ARCHITECTURAL & SPECIFICATION LIGHTING |
| Type | RECESSED |

Availability

| | |
|--------|----------|
| Status | Inactive |
|--------|----------|

Packaging

| | |
|-----------------|-------|
| Carton | 1 |
| Weight Per each | 25.79 |

Uses, Certifications, and Standards

| | |
|-------------|----------|
| Application | lighting |
| Mounting | Recessed |