

ELLIOTT ELECTRIC SUPPLY 1510 East Interstate 30 75087-0000, TX Rockwall

We Deliver...Lower Cost, Quality Products, & Personal Service

Phone: 469-913-1945 Fax: 469-913-1946



251MSRT 3/4" Raintight Push Emt Connector *Nsi Industries*

Catalog Number	251MSRT
Manufacturer	Nsi Industries
Description	Bridgeport Fittings Mighty-Seal« 3/4 Inch Emt Connectors Are Used to Connect A 3/4 Inch Emt Raceway to A Box, Device or Enclosure. The 251MSRT 3/4 Inch Mighty-Seal Connector Is UI
Weight per unit	Listed For Use In Wet Locations. Raintight. Patented 0.1680 (lbs/each)
Product Category	Die Cast Uninsulated Straight

Features

PUSH-EMT® Connector Type insulation False media Yes

Material, Color, and Finish

Ball burnish Finish

Dimensions and Weight

Size 3/4

Descriptions

3/4" RAINTIGHT PUSH EMT CONNECTOR
BPT 251-MSRT 3/4" PUSH-EMT MSRT CON
Time Saver: All it takes is a push! 75% quicker install. No tools required. Removable and Raintight!
Bridgeport Fittings Mighty-Seal « 3/4 inch EMT Connectors are used to connect a 3/4 inch EMT raceway to a box, device or enclosure. The 251MSRT 3/4 inch Mighty-Seal connector is UL listed for use in wet locations. Raintight. Patented
3/4" Push-Emt MSRT Conn
Connectors assembled with knockout gasket, no separate pieces to buy and stock

Manufacturer Information

Brand	Bridgeport Fittings
GTIN	00781747172518
Manufacturers Part Number	251-MSRT
UPC	781747172518

Taxonomies, Classifications, and Categories

Category Description	DIECAST EMT FITTINGS
Туре	CONNECTOR

Trade Size

Trade Size 3/4



ELLIOTT ELECTRIC SUPPLY 1510 East Interstate 30 75087-0000, TX Rockwall Phone: 469-913-1945 Fav: 460-913-1946

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 469-913-1946

	Packaging
--	-----------

Carton	25	
Package	250	
Weight Per each	0.168	

Uses

es, Certifications, and Standards	
Application	Bridgeport Fittings Mighty-Seal® 3/4 inch EMT Connectors are used to connect a 3/4 inch EMT raceway to a box, device, or
	enclosure. The 251-MSRT 3/4 inch Mighty-Seal® connector is UL
	listed for use in wet locations.
standard	cULus