



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



256SRTI 2-1/2" Ins Steel Emt Raintight Compression Conn

Nsi Industries

| | |
|------------------|---|
| Catalog Number | 256SRTI |
| Manufacturer | Nsi Industries |
| Description | Connector, Compression, Steel, Insulated Throat - 105 Degree C, Size 2 1/2" |
| Weight per unit | 1.6 (lbs/each) |
| Product Category | Steel Insulated Straight Compr |

Features

| | |
|----------------|--|
| Connector Type | Steel Raintight/Concrete-Tight Insulated |
| insulation | Insulated Throat |
| media | Yes |

Material, Color, and Finish

| | |
|--------|--------------------|
| Finish | Zinc Electroplated |
|--------|--------------------|

Dimensions and Weight

| | |
|------|-------|
| Size | 2-1/2 |
|------|-------|

Descriptions

| | |
|------------------------|--|
| Description | 2-1/2" INS STEEL EMT RAINLIGHT COMPRESSION CONN |
| extra long description | BPT 256-SRTI 2-1/2" STEEL RAINLIGHT |
| Features | Think Orange: Quality In, Water Out. Listed for Damp or Wet Locations. |
| Long Description | Connector, Compression, Steel, Insulated Throat - 105 Degree C, size 2 1/2" |
| Product Type | 2-1/2" Steel Raintight Conn, I |
| Special Features | Connectors assembled with knockout gasket, no separate pieces to buy and stock |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Bridgeport |
| GTIN | 00781747122568 |
| Manufacturers Part Number | 256-SRTI |
| UPC | 781747122568 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------|
| Category Description | STEEL EMT FITTINGS |
| Type | CONNECTOR |

Trade Size

| | |
|------------|-------|
| Trade Size | 2-1/2 |
|------------|-------|



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|------|
| Carton | 2 |
| Package | 10 |
| Weight Per each | 1.61 |

Uses, Certifications, and Standards

| | |
|-------------|---|
| Application | Used to join EMT to box or enclosure. Concrete/Raintight. Insulated Throat - 105°C. Patented |
| standard | cULus |