



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

9172 E Florentine Road Unit 9
86314-0000, AZ Prescott Valley
Phone: 928-356-1174
Fax: 480-426-8084



257RTI2 3" Raintight Diecast Compression Connector

Nsi Industries

| | |
|------------------|--|
| Catalog Number | 257RTI2 |
| Manufacturer | Nsi Industries |
| Description | 3" Raintight Insulated Connector, NPT Thread |
| Weight per unit | 1.7 (lbs/each) |
| Product Category | Liquid Tight Fittings |

Features

| | |
|----------------|------------------|
| Connector Type | Compression |
| insulation | Insulated Throat |
| media | Yes |

Dimensions and Weight

| | |
|------|---|
| Size | 3 |
|------|---|

Descriptions

| | |
|------------------------|--|
| Description | 3" RAINLIGHT DIECAST COMPRESSION CONNECTOR |
| extra long description | BPT 257-RTI2 3" RAINLIGHT INS CONNE |
| Features | Think Orange: Quality In, Water Out. Listed for Damp or Wet Locations. |
| Long Description | 3" Raintight Insulated Connector, NPT THREAD |
| Product Type | 3" Raintight Ins Connector |
| Special Features | The Dual Internal sealing rings create a raintight seal. |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Bridgeport |
| GTIN | 00781747192578 |
| Manufacturers Part Number | 257-RTI2 |
| UPC | 781747192578 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------|
| Category Description | METALLIC FITTINGS |
| Type | Raintight Compression |

Trade Size

| | |
|------------|---|
| Trade Size | 3 |
|------------|---|

Packaging

| | |
|-----------------|-------|
| Carton | 12 |
| Weight Per each | 1.725 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

9172 E Florentine Road Unit 9
86314-0000, AZ Prescott Valley
Phone: 928-356-1174
Fax: 480-426-8084

Uses, Certifications, and Standards

Application

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure. With Bridgeport's newly redesigned Raintight Compression Connectors, 256-RTI2 thru 259-RTI2, contractors can install just one wet location fitting for either thread less Rigid / IMC or EMT. These 3" dual Listed Zinc Alloy fittings come standard with a 105° C temperature rated insulated throat and the words "Rigid / EMT and RAINTIGHT" clearly cast into the body. Thi

standard

cULus