

ELLIOTT ELECTRIC SUPPLY 7604 Gateway Blvd 77521-0000, TX Baytown Phone: 832-514-7819 Fax: 832-514-7820



Trade Size

259DCI2 4" Diecast Emt Insulated Concrete Tight Conn *Nsi Industries*

Catalog Number Manufacturer Description Weight per unit Product Category	259DCI2 Nsi Industries Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 4 Inch 3.0 (lbs/each) Die Cast Insulated Straight CO
Description Weight per unit	Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 4 Inch 3.0 (lbs/each)
Weight per unit	Throat, Size 4 Inch 3.0 (lbs/each)
Product Category	Die Cast Insulated Straight CO
····	
eatures	
Connector Type	Compression
insulation	Insulated Throat
media	Yes
aterial, Color, and Finish Finish	Ball burnish
	Dali Dullisii
mensions and Weight Size	4
escriptions	
Description	4" DIECAST EMT INSULATED CONCRETE TIGHT CONN
extra long description	BPT 259-DCI2 4" COMP. CONN. INS.
Features	Think Orange: Zinc Advantage –Error-free Performance – meets same stringent UL tests as steel. Bridgeport zinc EMT fittings set the standard for EMT.
Long Description	Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 4 Inch
Product Type	4" Comp. Conn. Ins.
Special Features	Concrete-Tight
anufacturer Information	
Brand	Bridgeport
GTIN	007017471/000
Manufacturers Part Number	259-DCI2
UPC	781747162595
exonomies, Classifications, and Categ	ories
	DIECAST EMT FITTINGS
Туре	
ade Size	



ELLIOTT ELECTRIC SUPPLY 7604 Gateway Blvd 77521-0000, TX Baytown Phone: 832-514-7819 Fax: 832-514-7820

Packaging	
Weight Per each	3
Uses, Certifications, and Standards	
Application	Used to join steel EMT to box or enclosure. Concrete-tight. 2 1/2" thru 4" suitable for use with Steel EMT. Insulator rated 105°C. 2-1/2" through 4" also listed for use with Steel and Aluminum Rigid Conduit.
standard	cULus