

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Trade Size

259DCI2 4" Diecast Emt Insulated Concrete Tight Conn *Bridgeport Fittings*

Catalog Number	259DCl2
Manufacturer	Bridgeport Fittings
Description	Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 4 Inch
Weight per unit	3.0 (lbs/each)
Product Category	Die Cast Insulated Straight CO
eatures	
Connector Type	Compression
insulation	Insulated Throat
media	Yes
Material, Color, and Finish Finish	Ball burnish
	Dull Dull Holl
Dimensions and Weight Size	4
Descriptions	
Description	4" DIECAST EMT INSULATED CONCRETE TIGHT CONN
extra long description	BPT 259-DCI2 4" COMP. CONN. INS.
Features	Think Orange: Zinc Advantage –Error-free Performance – meets same stringent UL tests as steel. Bridgeport zinc EMT fittings set the standard for EMT.
Long Description	Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 4 Inch
Product Type	4" Comp. Conn. Ins.
Special Features	Concrete-Tight
Manufacturer Information	
Brand	Bridgeport
GTIN	00781747162595
Manufacturers Part Number	259-DCI2
UPC	781747162595
axonomies, Classifications, and (Categories
Category Description	
Туре	
rade Size	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	6
Weight Per each	3
Uses, Certifications, and Standards	
Application	Used to join steel EMT to box or enclosure. Concrete-tight. 2
	1/2" thru 4" suitable for use with Steel EMT. Insulator rated
	105°C. 2-1/2" through 4" also listed for use with Steel and
	Aluminum Rigid Conduit.
standard	cULus