




ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



259RTI2 4" Raintight Compression Connector

Nsi Industries

| | |
|------------------|--|
| Catalog Number | 259RTI2 |
| Manufacturer | Nsi Industries |
| Description | 4" Raintight Insulated Connector, NPT Thread |
| Weight per unit | 2.6 (lbs/each) |
| Product Category | Die Cast Uninsulated Straight |

Features

| | |
|----------------|------------------|
| Connector Type | Compression |
| insulation | Insulated Throat |
| media | Yes |

Dimensions and Weight

| | |
|------|---|
| Size | 4 |
|------|---|

Descriptions

| | |
|------------------------|--|
| Description | 4" RAINTIGHT COMPRESSION CONNECTOR |
| extra long description | BPT 259-RTI2 4" RAINTIGHT INS CONNE |
| Long Description | 4" Raintight Insulated Connector, NPT THREAD |
| Product Type | 4" Raintight Ins Connector |
| Special Features | The Dual Internal sealing rings create a raintight seal. |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Bridgeport |
| GTIN | 00781747192592 |
| Manufacturers Part Number | 259-RTI2 |
| UPC | 781747192592 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------|
| Category Description | DIECAST EMT FITTINGS |
| Type | Raintight Compression |

Trade Size

| | |
|------------|---|
| Trade Size | 4 |
|------------|---|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 6 |
| Weight Per each | 2.64 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure. With Bridgeport's newly redesigned Raintight Compression Connectors, 256-RTI2 thru 259-RTI2, contractors can install just one wet location fitting for either thread less Rigid / IMC or EMT. These 4" dual Listed Zinc Alloy fittings come standard with a 105° C temperature rated insulated throat and the words "Rigid / EMT and RAIN TIGHT" clearly cast into the body. Thi

standard

cULus