

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685

Wido.

## 30026 Noalox (4 Oz. Bottle)

Catalog Number	30026
Manufacturer	Ideal
Description	A 1! O.

Anti-Oxidant Compound, 4 Oz Squeeze Bottle, Petroleum Base, Description 1.04 Specific Gravity, 310 °F Flash Point, 0.33 LB

0.3250 (lbs/each) Weight per unit

Product Category Paint, Chemicals, Etc.

**Features** 

specific gravity 1.04

**Dimensions and Weight** 

Size 4 OZ Squeeze Bottle

**Descriptions** 

Description NOALOX (4 OZ. BOTTLE)

extra long description IDEAL 30-026 NOALOX (4 OZ CONTAINER

**Features** IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service

entrances and split-bolts. It is used with all types of pressure-type

wire connectors.

Anti-oxidant and anti-seizing compound improves efficiency and Special Features

service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service

life of aluminum ele

**Manufacturer Information** 

Brand Ideal **GTIN** 00783250300266 **UPC** 783250300266

**Taxonomies, Classifications, and Categories** 

Category Description WIRE LUBE, MARKERS, & TIES **Anti-Oxidant Compound** Type



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	10
Weight Per each	0.325
Uses, Certifications, and Standards	
standard	UL Listed