

ELLIOTT ELECTRIC SUPPLY 2501 S. Fort Hood St. 76542-2312, TX Killeen Phone: 254-554-5958

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 254-554-8423



30092J Greenie Grounding Wire Conn, 92 Green, 150/Jar *Ideal*

W .	
Catalog Number	30092J
Manufacturer	ldeal
Description	Ideal, Grounding Wire Connector, Greenie, Twist-On, Number Of Conductors: 2 to 5, Conductor Range: 14 - 10 Awg, Min 2 - 14, Max 4-12, Color: Green, Material: Polypropylene, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell, Model Number: 92, Width: 29/32 In, Height: 1-5/32 In, Flammability Rating: UI 94V-2
Weight per unit	N/A
Product Category	Electrical Fixture Conn (Nuts
Features	
Material	Polypropylene
Voltage Rating	600
Material, Color, and Finish Color	Green



ELLIOTT ELECTRIC SUPPLY 2501 S. Fort Hood St. 76542-2312, TX Killeen Phone: 254-554-5958

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 254-554-8423

_			•			
De	~~	ヘr	ı	۱t.	$\mathbf{\Lambda}$	nc
	_					
_	-	v.		,,,	•	
			•			

GREENIE GROUNDING WIRE CONN, 92 GREEN, 150/JAR
IDEAL 30-092J GREENIE GROUNDING 92,
The Wing-Nut Wire Connector provides an easy, secure grip when connecting a wide range of wires. The specially designed contoured wings make for extra torque and quick work on any electrical job. The wide range, live-action spring is flexible enough to handle small combinations with ease but then expands to accept large combinations when you need it. It can also be reused on same size or larger combinations for quick and easy circuit changes and additions. The Wing-Nut also features a tough, copolymer, flam
IDEAL, Grounding Wire Connector, Greenie, Twist-On, Number Of Conductors: 2 to 5, Conductor Range: 14 - 10 AWG, Min 2 - 14, MAX 4-12, Color: Green, Material: Polypropylene, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell, Model Number: 92, Width: 29/32 IN, Height: 1-5/32 IN, Flammability Rating: UL 94V-2
Greenie Grounding 92, 150 Jar
Complies With Federal Specification W-S-610E; Contoured Wings For Maximum Leverage; Features: Designed For Making Ground Connections And Bonding Non-Metallic Sheathed Cable; Flammability Rating: UL 94V-2; Height: 1-5/32 IN; Live-Action, Square-Wire Spring Provides Superior Grounding Connections; Model Number: 92; Tough, UL 94V-2 Flame-Retardant Shell; UL Listed To 467 And CSA Certified To C22.2 #188; Width: 29/32 IN

Mai

Brand	ldeal
GTIN	00783250541232
Manufacturers Part Number	30-092J
UPC	783250541232

Taxonomies, Classifications, and Categories

Category Description	WIRE NUTS
Туре	Twist-On

Availability

•	
minimum gty	150

Packaging

Carton	150	
Package	900	
Weight Per each	0	

2501 S. Fort Hood St. 76542-2312, TX Killeen Phone: 254-554-5958 Fax: 254-554-8423

Uses, Certifications, and Standards

Application	Insulating or Joining 2 or more conductors
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell
standard	CSA Certified to C22.2 #188, UL Listed to 467, complies with
	Federal Specification W-S-610E, RoHS Compliant