

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7929 N Sam Houston Pkwy W Suite 100 77064-0000, TX Houston Phone: 281-345-1143

Fax: 281-345-7697



Availability

minimum qty

301263J Weatherproof Wire Conn, 63 Gray/DK Blue, 50/Jar *Ideal*

Ideal	
Catalog Number	301263J
Manufacturer	Ideal
Description	Model 63 Gray Blue 50 Jar
Weight per unit	0.0260 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
eatures	
media	Yes
Quantity	Jar of 50
Material, Color, and Finish	
Color	Gray
Descriptions	
Description	WEATHERPROOF WIRE CONN, 63 GRAY/DK BLUE, 50/JAR
extra long description	IDEAL 30-1263J WP MODEL 63 GRAY BLU
Features	100% Silicone-based sealant protects against moisture and
	corrosionUL Listed to 486G Sealed Twist-On Wire Connector for
	use in damp/wet locations or above-grade applicationsEasy to
	apply, pre-filled twist-on wire connectorsSwept wing design is
	built for comfort and efficiencyEliminates the need for
	heat-shrink or excessive tapingTough, UL 94V-2 flame-retardant
	shell rated at 105°C (221°F)Models 61 and 63 approved for
	bonding and grounding applicationsFor use in damp/wet location
	or above-grade applications
Long Description	MODEL 63 GRAY BLUE 50 JAR
Product Type	WP Model 63 Gray Blue 50 Jar
Special Features	Silicone-based sealant protects against moisture and corrosion.
	Easy to apply pre-filled twist-on wire connectors
/lanufacturer Information	
Brand	ldeal
GTIN	00783250756377
Manufacturers Part Number	30-1263J
UPC	783250756377
axonomies, Classifications, and (Categories
Category Description	WIRE NUTS
Туре	Model 63® Connector

50



ELLIOTT ELECTRIC SUPPLY We Deliver...Lower Cost, Quality Products, & Personal Service 7929 N Sam Houston Pkwy W Suite 100 77064-0000, TX Houston Phone: 281-345-1143 Fax: 281-345-7697

Packaging	
Carton	50
Weight Per each	0.026
Uses, Certifications, and Standards	
Application	Handles wire sizes from #16 to #6 AWG copper. Minimum of 3
	#14 AWG. Maximum of 2 #8 & 1 #10 AWG
standard	UL listed for 486D for use in damp/wet locations