

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3101 Industrial Terrace 78758-0000, TX Austin Phone: 512-351-3290

Fax: 512-973-9027



30451 Wing-Nut Wire Conn, Model 451 Yellow, 100/Box

Catalog Number	30451
Manufacturer	ldeal
Description	Twist-On Wingnut, Yellow Insulation Color, +221 °F Operating
	Temperature, 1 to 6 Conductors, 600 V Ac, 0.45 LB
Weight per unit	0.0050 (lbs/each)
Product Category	Electrical Fixture Conn (Nuts
tures	

Features

Material	Flame-retardant polypropelene shell	
media	Yes	
Voltage Rating	600	

Material, Color, and Finish

Color Yellow

Descriptions

Description	WING-NUT WIRE CONN, MODEL 451 YELLOW, 100/BOX
extra long description	IDEAL 30-451 WINGNUT 451 YELLOW, 10
Features	Largest range in the Industry - from 2 #18 to up 4 #10High-leverage, contoured wing provides superior torque on every twistWide range, live-action spring handles small combinations and expands to accommodate large combinations as you need itCopolymer shell expands for smooth, progressive tightening providing dependable connectionsRemovable for repeat usage on same size or larger combinationsMore power with every twist.The Wing-Nut Wire Connector provides an easy, secure grip when connecting a wide range of
	Coodi o grip Wilori coming a Wido rango or

Manufacturer Information

Brand	Ideal	
GTIN	00783250304516	
UPC	783250304516	

Taxonomies, Classifications, and Categories

toriornics, diassinations, and outegories		
Category Description	WIRE NUTS	
Туре	Twist-On	

Availability

minimum qty	100

Packaging

Carton	100	
Package	1000	
Weight Per each	0.005	

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3101 Industrial Terrace 78758-0000, TX Austin Phone: 512-351-3290 Fax: 512-973-9027

Uses, Certifications, and Standards

Application	Insulating or Joining 2 or more conductors
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F)
standard	CSA Certified to C22.2 #188, UL Listed to 486C, complies with
	Federal Specification W-S-610E, RoHS Compliant