

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1550 Wilson Rd. 77338-0000, TX Humble Phone: 281-548-0169 Fax: 281-548-0198



## 306064 Underground Wire Conn, 60/64, 5 Of Each, 10/Card Ideal

Ideal 60 64 Undergrd 10 Clam 0.0200 (lbs/each) Plugs, Connectors, Inlets, Out  Card of 10
0.0200 (lbs/each) Plugs, Connectors, Inlets, Out
Plugs, Connectors, Inlets, Out
· ·
Card of 10
Card of 10
0414 01 10
Gray
UNDERGROUND WIRE CONN, 60/64, 5 OF EACH, 10/CARD
IDEAL 30-6064 60 64 UNDERGRD COMBO,
100% Silicone-based sealant protects against moisture and corrosionUL Listed to 486G Sealed Twist-On Wire Connector for use in damp/wet locations or above-grade applicationsEasy to apply, pre-filled twist-on wire connectorsExpanding, live-action square-wire spring for fast, secure and long-lasting connectionsDeep skirt provides superior moisture resistance to protect connectionsTough, UL 94V-2 flame-retardant shell rated at 105°C (221°F)For use in damp/wet location or direct burial/below-grade applications
60 64 UNDERGRD 10 CLAM
60 64 Undergrd Combo, 10 Clam
Smallest wet location/direct burial connector with widest wire range. Non-hardening sealant completely seals out moisture to protect fungus and corrosion. Sealant is stable down to -40° C. Flame-retardant Shell

## Manufacturer Information

Brand	Ideal
GTIN	00783250758173
Manufacturers Part Number	30-6064
UPC	783250758173



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1550 Wilson Rd. 77338-0000, TX Humble Phone: 281-548-0169 Fax: 281-548-0198

<b>Taxonomies, Classifications, and Categ</b>	
Category Description	WIRE NUTS
Туре	Model 60® & Model 64® Combo Pack
Availability	
minimum qty	10
Packaging	
Carton	10
Package	50
Weight Per each	0.02
Uses, Certifications, and Standards	
Application	Model 60® Handles wire sizes from #20 to #10 AWG copper.  Model 60® Minimum of 1 #20 with 1 #18. Model 60® Maximum
	of 2 #12 & 1 #10 AWG. Model 64® Handles wire sizes from #18 to
	#8 AWG copper. Model 64® Minimum of 2 #18 AWG. Model 64® Maximum of 2 #10 AWG

**UL Listed & CSA certified**