

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

1135 Butler Road 77573-0000, TX League City Phone: 281-833-5333 Fax: 281-833-5334

31358 Yellow 77, 1-Qu Ideal	art Squeeze Bottle
Catalog Number	31358
Manufacturer	Ideal
Description	Lubricant, 1 QT Squeeze Bottle, Slight Perfume Odor, Yellow 77 Lubricant, 0.98 Specific Gravity, +40 to +100 °F, 2.31 LB
Weight per unit	2.3 (lbs/each)
Product Category	Paint, Chemicals, Etc.
Dimensions and Weight Size	1
Descriptions	
Description	YELLOW 77, 1-QUART SQUEEZE BOTTLE
extra long description	IDEAL 31-358 YELLOW 77 QT. SQUEEZE
Features	IDEAL Yellow 77 Wire pulling lubricant is a wax-based formula, and is the perfect general purpose lube. It is safe to use with most cable types except low-density polyethylene and semi-conducting jackets. It won't break down/separate after repeated exposure to freezing temperatures and dries to a thin, non-conductive film that won't clog conduit. Yellow 77 has a creamy texture and clings to cable throughout long pulls. Apply conveniently and uniformly by hand or brush. It is a homogeneous blend that requir
Special Features	The #1 brand of wire pulling lubricant since 1959 - the perfect general purpose lube; Wax-based formula provides superior lubricity; Safe to use with most cable types except low-density polyethylene and semi-conducting jackets; Won't break down or separate after repeated exposure to freezing temperatures; Dries to a thin, non-conductive film that won't clog conduit; Clings to cable throughout long pulls; Easy to apply by hand or with pump; Creamy texture applies easily and uniformly; Homogeneous blend requ
Manufacturer Information Brand	Ideal
GTIN	00783250313587
UPC	783250313587
Taxonomies, Classifications, and Cate	
Category Description	•
Turne	Lubricont
Туре	Eddition



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

1135 Butler Road 77573-0000, TX League City Phone: 281-833-5333 Fax: 281-833-5334

Packaging

Uses, Certifications, and Standards

	standard	
--	----------	--

UL	Listed					
UL	Listed					