



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3706 Frankston Hwy
75701-0000, TX Tyler
Phone: 903-509-9882
Fax: 903-509-9832



31378 Aqua-Gel II, 1-Quart Squeeze Bottle

Ideal

Catalog Number	31378
Manufacturer	Ideal
Description	Lubricant, 1 QT Squeeze Bottle, Clear Blue, Mild Odor, Aqua-Gel II Lubricant, 0.98 Specific Gravity, +40 to +100 °F, 2.32 LB
Weight per unit	2.3 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Dimensions and Weight

Size	1
------	---

Descriptions

Description	AQUA-GEL II, 1-QUART SQUEEZE BOTTLE
extra long description	IDEAL 31-378 Aqua-Gel Lubricant, Ide
Features	IDEAL Aqua-Gel II Non-toxic cable pulling lubricant in clear blue color is a polymer-based formula that offers maximum tension reduction in high-stress electrical and communications cable-pulling operations. Lubricant dries to a semi-fluid film that won't clog conduit, and cleans up easily with soap/water. It remains temperature stable over a wide temperature range from 28°F to 180°F (-2°C to 88°C). Lubricant is convenient to apply by hand, brush or pump. It is well suited with all cable types except compo
Special Features	Polymer-based formula provides maximum tension reduction in high-stress electrical and communication cable-pulling operations; Compatible with all cable types except composite rubber; Cleans up easily with soap and water; Clings to cable throughout long pulls; Remains stable over wide temperature range; Dries to a semi-fluid film that won't clog conduit; Easy to apply by hand, brush or pump; Environmentally safe - non-toxic, non-flammable and non-corrosive; For outdoor use only

Manufacturer Information

Brand	Ideal
GTIN	00783250313785
UPC	783250313785

Taxonomies, Classifications, and Categories

Category Description	WIRE LUBE, MARKERS, & TIES
Type	Lubricant

Packaging

Carton	1
Package	12
Weight Per each	2.3167



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3706 Frankston Hwy
75701-0000, TX Tyler
Phone: 903-509-9882
Fax: 903-509-9832

Uses, Certifications, and Standards

standard

UL Listed