



350SR 350 Al/Cu Mechanical Butt Splice

Nsi Industries

Catalog Number	350SR
Manufacturer	Nsi Industries
Description	Aluminum Splicer Reducer 350 MCM - 6 Awg Aluminum Splicer Reducers Are Used For Splicing Two Copper or Aluminum Wires Of Equal or Different Sizes. Made Of 6061T-6 Aluminum Alloy. Electro-Tin Plated For Low Contact Resistance. Suitable For Use With Both Copper and Aluminum Conductors. Rated 600 Volts (2000V Max. Per UL486B). UL 486A/B Listed. Temperature Rating 90 Degrees C.
Weight per unit	0.3400 (lbs/each)
Product Category	Splicing & Terminating Kits

Features

Warranty	1 YEAR
----------	--------

Descriptions

Description	350 AL/CU MECHANICAL BUTT SPLICE
extra long description	NSI 350SR Splicer/Reducer 350-6
Features	Aluminum Splicer Reducer 350 MCM - 6 AWG Aluminum Splicer Reducers are used for splicing two copper or aluminum wires of equal or different sizes. Made of 6061T-6 aluminum alloy. Electro-tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600 volts (2000V max. per UL486B). UL 486A/B Listed. Temperature rating 90 degrees C.
Long Description	Aluminum Splicer Reducer 350 MCM - 6 AWG Aluminum Splicer Reducers are used for splicing two copper or aluminum wires of equal or different sizes. Made of 6061T-6 aluminum alloy. Electro-tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600 volts (2000V max. per UL486B). UL 486A/B Listed. Temperature rating 90 degrees C.
Product Type	Splicer/Reducer 350-6

Manufacturer Information

Brand	NSI
GTIN	00662381002341
Manufacturers Part Number	350SR
UPC	662381002341

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
----------------------	-------------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 W. Esthner Avenue
67213-0000, KS Wichita
Phone: 316-854-0028
Fax: 316-854-0029

Packaging

Carton	1
Package	8
Weight Per each	0.34