



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 3852 Straight Blade Recp 2P Wire 50AMP 250V

*Pass & Seymour/Legrand*

|                  |  |
|------------------|--|
| Catalog Number   | 3852   |
| Manufacturer     | Pass & Seymour/Legrand   |
| Description      | Straight Blade Receptacle, 50 A, 250 V Ac, 2 Poles, 3 Wires, Wire Ground Connection, Wall Mount, 2.8 In Length, 5.65 In Height, Thermoplastic, Black, Arc Resistant, 1.0900 LB |
| Weight per unit  | 1.1 (lbs/each)   |
| Product Category | Gen Purpose Recept & Surge Pro   |

### Features

|                 |             |
|-----------------|-------------|
| amperage rating | 50          |
| connection      | Wire Ground |
| Poles           | 2           |
| Voltage         | 250.0 V     |
| Wire Size       | 4           |

### Dimensions and Weight

|      |        |
|------|--------|
| Size | 5.7 in |
|------|--------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | STRAIGHT BLADE RECP 2P WIRE 50AMP 250V |
| extra long description | P&S 3852 STR BLD RECPT 2P WIRE 50AM    |

### Manufacturer Information

|       |                  |
|-------|------------------|
| Brand | Pass and Seymour |
| GTIN  | 00785007791853   |
| UPC   | 785007791853     |

### Taxonomies, Classifications, and Categories

|                      |                           |
|----------------------|---------------------------|
| Category Description | Residential receptacles   |
| Type                 | Straight Blade Receptacle |

### Trade Size

|          |      |
|----------|------|
| Amperage | 50.0 |
|----------|------|

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Package         | 10    |
| Weight Per each | 1.088 |

### Uses, Certifications, and Standards

|          |                   |
|----------|-------------------|
| Mounting | WALL              |
| standard | CULUS, UL, UL 498 |