



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



390 4" Malleable Insulated Grounding Bushing

Nsi Industries

Catalog Number	390
Manufacturer	Nsi Industries
Description	Bushing, Insulated, Grounding, Malleable Iron, Size 4 Inch, 14-1/0 Lug
Weight per unit	1.0 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

Material	Malleable Iron
media	Yes

Material, Color, and Finish

Color	Grey with Black Insulator
Finish	Zinc Electroplated

Dimensions and Weight

Size	4
------	---

Descriptions

Description	4" MALLEABLE INSULATED GROUNDING BUSHING
extra long description	BPT 390 4 IN Grd.Bush.Ins. 14-1/0 M
Long Description	Bushing, Insulated, Grounding, Malleable Iron, Size 4 Inch, 14-1/0 Lug
Product Type	4 In GRD.Bush.Ins. 14-1/0 Mall, Box Of 20
Special Features	Grounding Lug Wire Capacity #14 - #1/0

Manufacturer Information

Brand	Bridgeport
GTIN	00781747003904
UPC	781747003904

Taxonomies, Classifications, and Categories

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Type	BUSHING

Trade Size

Trade Size	4
------------	---

Packaging

Carton	20
Weight Per each	1



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum alloy 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.

standard

cULus

Temperature Rating

150°C