


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

221 Hord St 70123-0000, LA Harahan Phone: 504-264-9995





391 5" Malleable Insulated Grounding Bushing *Nsi Industries*

Catalog Number	391
Manufacturer	Nsi Industries
Description	Bushing, Insulated, Grounding, Malleable Iron, Size 5 Inch
Weight per unit	
	Rigid Conduit Fittings - Steel
Features	
Material	Malleable Iron
media	Yes

Material, Color, and Finish

Color	Grey with Black Insulator
Finish	Zinc Electroplated
FILLISH	/IIIC FIECH ODIATED

Dimensions and Weight

Size	ļ
SIZC	

Descriptions

Description	5" MALLEABLE INSULATED GROUNDING BUSHING
extra long description	BPT 391 5" GRND. BUSH. INS.
Long Description	Bushing, Insulated, Grounding, Malleable Iron, Size 5 Inch
Product Type	5" GRND. Bush. Ins.
Special Features	Grounding Lug Wire Capacity #6 - #250 MCM

Manufacturer Information

Brand	Bridgeport
GTIN	00781747003911
UPC	781747003911

Taxonomies, Classifications, and Categories

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding
	Fittings & Ground Rods
Туре	BUSHING
Trade Size	
Trade Size	5

Packaging

Carton 5 Weight Per each 1.48	okuging		
Weight Per each 1.48	Carton	5	
	Weight Per each	1.48	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

221 Hord St 70123-0000, LA Harahan Phone: 504-264-9995 Fax: 504-264-5996

Uses, Certifications, and Standards

Application	Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum allog 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.
standard	cULus
Temperature Rating	150?°C