



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



392 6" Malleable Insulated Grounding Bushing

Nsi Industries

Catalog Number	392
Manufacturer	Nsi Industries
Description	Bushing, Insulated, Grounding, Malleable Iron, Size 6 Inch
Weight per unit	0.4240 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

Material	Malleable Iron
media	Yes

Material, Color, and Finish

Color	Grey with Black Insulator
Finish	Zinc Electroplated

Dimensions and Weight

Size	6
------	---

Descriptions

Description	6" MALLEABLE INSULATED GROUNDING BUSHING
extra long description	BPT 392 6" GRND. BUSH. INS.
Long Description	Bushing, Insulated, Grounding, Malleable Iron, Size 6 Inch
Product Type	6" GRND. Bush. Ins.
Special Features	Grounding Lug Wire Capacity #6 - #250 MCM

Manufacturer Information

Brand	Bridgeport
GTIN	00781747003928
UPC	781747003928

Taxonomies, Classifications, and Categories

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Type	BUSHING

Trade Size

Trade Size	6
------------	---

Packaging

Carton	5
Weight Per each	0.424



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum alloy 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.

standard

cULus

Temperature Rating

150°C