

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2001 ATKINSON DRIVE 75901-0000, TX Lufkin Phone: 936-632-9733 Fax: 936-632-9736



4150ST 1-1/2 In Emt SSCR Conn Insul Steel

Appleton/Oz Gedney

40	
Catalog Number	4150ST
Manufacturer	Appleton/Oz Gedney
Description	Features:1 15/16IN Dia X 1 15/16IN Length, 9/16 In Thread Length, Concretetight, Standard:UI 514B, Csa C22.2, Nema FB-1, Size:1.5IN, Connection:Male NPS Thread, Material:Steel, Finish:Zinc Electro Plated, Insulation:Insulated Throat, Temperature Rating:90C
Weight per unit	0.5000 (lbs/each)
Product Category	Steel Insulated Straight Set S
Features	
connection	Male NPS Thread
Connector Type	SET SCREW
insulation	Insulated Throat
Material	Steel
Material, Color, and Finish	
Color	Metallic
Finish	Zinc Electro Plated

Mat

Color	Metallic
Finish	Zinc Electro Plated

Dimensions and Weight

Size	1.,

Descriptions

Description	1-1/2 IN EMT SSCR CONN INSUL STEEL
extra long description	EGS 4150ST 1-1/2 IN EMT SSCR CONN I
Long Description	Features:1 15/16IN Dia X 1 15/16IN Length, 9/16 IN Thread Length, Concretetight, Standard:UL 514B, CSA C22.2, NEMA FB-1, Size:1.5IN, Connection:Male NPS Thread, Material:Steel, Finish:Zinc Electro Plated,Insulation:Insulated Throat, Temperature Rating:90C
Product Type	1-1/2 In Emt SSCR Conn Insul Steel
Special Features	1-1/2 IN Trade Size Connector for EMT Conduit, Set Screw Type, Male Hub Threads NPS, Body Length 1.94 IN, Max. Dia. 1.94 IN,Thread Length 0.56 IN, Concretetight when taped, Male Hub Threads - NPS, Insulated Throat

Manufacturer Information

Brand	Appleton/Oz Gedney
GTIN	00687855846238
Manufacturers Part Number	4150ST
UPC	687855846238



ELLIOTT ELECTRIC SUPPLY 2001 ATKINSON DRIVE 75901-0000, TX Lufkin Phone: 936-632-9733 Fax: 936-632-9736

Taxonomies, Classifications, and Cate	
Туре	EMT Conduit Straight Set Screw Connector
Trade Size	
Trade Size	1.5
Packaging	
Carton	1
Weight Per each	0.5
Uses, Certifications, and Standards	
Application	To ground and secure EMT Raceways to boxes and enclosures
nema rating	FB-1
standard	UL Standard: 514B; UL Listed: E14815, E14895; CSA Standard:
	C22.2 No. 18.3, cUL Listed: E14895, CSA Certified: 028507; NEMA: FB-1
Temperature Rating	90