



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



470LT12 1/2" 90D L/T Insul Throat Conn *Bridgeport Fittings*

| | |
|------------------|--|
| Catalog Number | 470LT12 |
| Manufacturer | Bridgeport Fittings |
| Description | Connector, Liquid Tight, 90 Degree, Die Cast Zinc, Insulated Throat, Size 1/2 Inch |
| Weight per unit | 0.0030 (lbs/each) |
| Product Category | Liquid Tight Fittings |

Features

| | |
|----------------|------------------------|
| angle | 90 DEG |
| Connector Type | LiquidTight, Insulated |
| Material | Zinc Cast |
| media | Yes |

Material, Color, and Finish

| | |
|--------|--------------------|
| Finish | Zinc Electroplated |
|--------|--------------------|

Dimensions and Weight

| | |
|------|-----|
| Size | 1/2 |
|------|-----|

Descriptions

| | |
|------------------------|--|
| Description | 1/2" 90D L/T INSUL THROAT CONN |
| extra long description | BPT 470-LT12 1/2" LQDT. CONN. INS. |
| Long Description | Connector, Liquid Tight, 90 Degree, Die Cast Zinc, Insulated Throat, Size 1/2 Inch |
| Product Type | 1/2" LQDT. Conn. Ins. |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Bridgeport |
| GTIN | 00781747164704 |
| Manufacturers Part Number | 470-LT12 |
| UPC | 781747164704 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------------|
| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS |
| Type | CONNECTOR |

Trade Size

| | |
|------------|-----|
| Trade Size | 1/2 |
|------------|-----|

Packaging

| | |
|-----------------|-------|
| Carton | 25 |
| Package | 100 |
| Weight Per each | 0.003 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

90 Degree connector for use with metallic and nonmetallic "Type B" liquid tight conduit. 3/8" thru 3/4" zinc die cast. Insulator rated 105 degree C.

standard

UL, CSA