Project	Catalog #	Туре	
Prepared by	Notes	Date	



Metalux

SHP-BTS

LED Shoplight with Bluetooth Speakers

Typical Applications

Portable Lighting • Workshops • Garages • Utility and Storage Rooms

♠ Interactive Menu

- Order Information page 2
- Photometric Data page 2
- Control Systems page 2
- Product Warranty

Product Certification



Product Features

Bluetooth

Top Product Features

- Lightweight, portable shoplight with fully integrated LEDs
- Integral luminaire speakers deliver a full, natural sound
- Easily listen to your favorite music or podcast wirelessly
- Wirelessly connect with any iOS or Android device
- 3800 nominal lumens, 4000K CCT at GreaterThan 80CRI

Dimensional and Mounting Details

Cross-section







Order Information

Catalog Number	Product Description	UPC	Unit Carton (L x W x H)
4SHP3240BTS	Shoplight LED 43" 3800L 4000K, 120V, BT Speaker	080083785612	45 x 4 x 3.3

Product Specifications

Electrical and Audio

- Fully integrated LED system, low wattage 120V electronic driver with on/off pull chain and 5ft grounded plug in cord provides a product for maximum portability and ease of use
- The integrated speakers utilize patented technology to deliver optimal acoustic performance in a compact and portable design
- The speakers can work independently with or without the light

Optics

- The SHP BTS uses 80CRI bright white 4000K LEDs enclosed behind a polycarbonate frost lens
- The LED and lens optics provide a uniform distribution and excellent color rendering

Wireless Connectivity

- Speakers connect wirelessly via Bluetooth, and work with both Android and iOS devices
- Easily listen to your favorite music or podcast wirelessly in your home or workshop

Compliance and Reliability

- · cULus listed for dry location
- Five-year comprehensive warranty
- TM21 projected lumen maintenance is L70 > 50,000 hours
- · FCC Class B and Energy Star Certified

Dimensional and Mounting Details Photometric Data View IES files Chain mount 32-3/4" [832mm] **4SHP3240BTS** 3 Prong Linear LED 4000K Cord Spacing criterion: 1.5M (II) 1.24 x mounting height, (\perp) 1.27 x mounting height Lumens: 3783 Input Watts: 31.1W Efficacy: 121.6 lm/W Test Report: 4SHP3240BTS.IES Speaker Surface mount 3 Prong Cord 1.5M Snapbrackets (Included)



Control Systems

- WaveLinx
- DLVP
- LumaWatt Pro
- iLumin Plus
- VividTune

Energy and Performance Data

Wattage

Model	Lumens	Wattage	
4SHP3240BTS	3782	31	

Shipping Data

Catalog No.	Weight per Carton	Units per Master Carton	Weight per Master Carton	Units per Pallet (40" x 48")
4SHP3240BTS	4.1 lbs.	2	8.2	72

Cooper Lighting Solutions 1121 Highway 74 South Peachtree City, GA 30269 P: 770-486-4800 www.cooperlighting.com