



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 541141337 3/4 NPS .625-.75 Nyl CRD Grip

*Remke Industries Inc.*

|                  |  |
|------------------|--|
| Catalog Number   | 541141337  |
| Manufacturer     | Remke Industries Inc.                                    |
| Description      | Cord Connector, Nylon, 3/4" NPS, Cable Range .625 - .750 |
| Weight per unit  | 0.1810 (lbs/each)  |
| Product Category | Cable & Cord Grips                                       |

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 3/4 NPS .625-.75 NYL CRD GRIP                            |
| extra long description | RMK RSP-212 Cord Grip nylon 3/4 in                       |
| Long Description       | Cord Connector, nylon, 3/4" NPS, cable range .625 - .750 |
| Product Type           | Cord Grip Nylon 3/4 In .625 - .750                       |

### Manufacturer Information

|                           |                  |
|---------------------------|------------------|
| Brand                     | Remke Industries |
| GTIN                      | 00785411413372   |
| Manufacturers Part Number | RSP-212          |
| UPC                       | 785411413372     |

### Taxonomies, Classifications, and Categories

|                      |                              |
|----------------------|------------------------------|
| Category Description | CORD CONNECTORS & CORD GRIPS |
|----------------------|------------------------------|

### Availability

|        |          |
|--------|----------|
| Status | Inactive |
|--------|----------|

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Weight Per each | 0.181 |

### Uses, Certifications, and Standards

|                          |                        |
|--------------------------|------------------------|
| environmental conditions | Flammability: UL 94V-2 |
|--------------------------|------------------------|