



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1220 Elm Street  
75482-0000, TX Sulphur Springs  
Phone: 903-885-0024  
Fax: 903-885-0352



## 54818 500MCM Brown 2WAY Cop Conn

*Abb Installation Products, Inc*

|                  |   |
|------------------|---|
| Catalog Number   | 54818   |
| Manufacturer     | Abb Installation Products, Inc  |
| Description      | Copper Two-Way Splice, Long Barrel, Max 35KV, 500 Kcmil, 925/24 Tin Plated, Die Code 87, Die Color Code Brown |
| Weight per unit  | 0.5000 (lbs/each)   |
| Product Category | Large Terminals & Connectors  |

### Features

|                |        |
|----------------|--------|
| Material       | Copper |
| Voltage Rating | 600 V  |

### Material, Color, and Finish

|        |            |
|--------|------------|
| Color  | Brown      |
| Finish | Tin-Plated |

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 500MCM BROWN 2WAY COP CONN  |
| extra long description | ABB 54818 2WAY CU SPLICE CONN LNGBR   |
| Long Description       | Copper Two-Way Splice, Long Barrel, Max 35kV, 500 kcmil, 925/24 Tin Plated, Die Code 87, Die Color Code Brown                                       |
| Product Type           | 2WAY Cu Splice Conn LNGBRL 500 BRN  |
| Special Features       | Two-Way Connectors Provide High Pullout Values, are Easy to Insulate and Provide a Low-Resistance Connection of High Quality and Low Installed Cost |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | COLOR-KEYED    |
| GTIN                      | 00786210548180 |
| Manufacturers Part Number | 54818          |
| UPC                       | 786210548180   |

### Taxonomies, Classifications, and Categories

|                      |                                   |
|----------------------|-----------------------------------|
| Category Description | Comp & Mech Lugs and Butt Splices |
| Type                 | Splice Connector                  |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 6   |
| Weight Per each | 0.5 |

### Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | Applications certified to 600 V and recommended up to 35 kV |
| standard    | UL E9809, CSA 4503 / UL E9809, CSA 4503                     |