



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 58027604 THHN 12 Sol Yellow 1000' Mini CP *Southwire Company*

Catalog Number	58027604
Manufacturer	Southwire Company
Description	600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant li. Rated Both THHN and THWN. Also Rated Awm. Simpull Technology For Easier Pulling.
Weight per unit	0.0200 (lbs/ft)
Product Category	THHN-T90-STR (Stranded)

### Features

Conductor Size	12
media	Yes
Number of Conductors	1
Voltage Rating	600

### Material, Color, and Finish

Insulation Material	PVC
Jacket Material	Nylon

### Dimensions and Weight

Length	1000
--------	------

### Descriptions

Description	THHN 12 SOL YELLOW 1000' MINI CP
extra long description	SWC 58027604 THHN 12 Sol Cu Yw 1000
Features	SIMPull THHN copper conductors are primarily used in conduit and cable trays for services, feeders and branch circuits in commercial or industrial applications as specified in the National Electrical Code. Voltage for all applications is 600 volts. SIMpull THHN copper conductors are designed to be installed without application of a pulling lubricant.
Long Description	600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated both THHN and THWN. Also rated AWM. SIMpull Technology for easier pulling.
Product Type	THHN 12 Sol Cu Yw 1000CP
Short Description	THHN 12 Sol Cu Yw 1000C
Special Features	No Lube



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	Copper
GTIN	00032886941115
Manufacturers Part Number	58027604
UPC	032886941115

## Taxonomies, Classifications, and Categories

Category Description	BUILDING WIRE
Type	THHN

## Packaging

Carton	1
Package	1000
Weight Per foot	0.02

## Uses, Certifications, and Standards

Application	Commerical
-------------	------------