

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



621143R1 Nuvo Wall Sconce

Catalog Number	621143R1
Manufacturer	Satco
Description	2 Light Led Large Up and Down Sconce Fixture - White Finish 20W 120/277V
Weight per unit	2.9 (lbs/each)
Product Category	Led Wall Mounted Architectural
atures	
beam angle	40

Feat

beam angle	40
Lamp Included	Integrated
Lamp Type	LED
lumens	1800
Material	Die Cast Aluminum
Number of Lamps	2
Socket Type	Integrated
Voltage Rating	120/277
Warranty	5 Year Limited - Fixtures
Wattage	20

Material, Color, and Finish

Color	White
color temperature	3000
fixture material	die-cast aluminum
Style	Utility

Dimensions and Weight

Height	11.69
Longth	3.35
Width	4.53

Descriptions

oriptions	
Description	NUVO WALL SCONCE
extra long description	SATCO 62/1143R1 2 LT LED LG UP DOWN
Long Description	2 Light LED Large Up and Down Sconce Fixture - White Finish 20W 120/277V
Product Type	2 LT Led LG Up Down Sconce 20W WH
Special Features	Warranty: 5-Years; Installation Notes: Mounts Up and Down; FCC Compliant: True; Photo Cell: No Photocell; Cct Selectable: False; CCT (Kelvin Temp): 3000K; Hours Rated: 50000; Beam Angle (degree): 40; Indoor Outdoor: Outdoor; IP Rating: IP65; Operating Temp: -30C (-22F) to +50C (+122F); Watts: 20W; Lumens: 1800L



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

м	١.	_		4	c _	_ 1				c _					
ľ	۱,	12	n	111		CI		·Δr	' In	ГЛ	rr	ทว	ıTI	n	n
	v			u	а	L - I	u	C-1	'In	W		110		w	

Brand	NUVO LIGHTING	
GTIN	00045923680892	
Manufacturers Part Number	62/1143R1	
UPC	045923680892	

Taxonomies, Classifications, and Categories

Category Description	LED ARCHITECTURAL & SPECIFICATION LIGHTING
Type	LED Decorative

Packaging

,g		
Carton	1	
Weight	2 51	
Weight Per each	2.916	

Uses, Certifications, and Standards

Application	Outdoor
Frequency Rating	50/60
Operating Temperature	-30C (-22F) to a maximum of +50C (+122F)
standard	cULus - Certified