

## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## 65043000 1" LFNC Orange Sealtight Southwire Company

Catalog Number Manufacturer	65043000 Southwire Company
Description	UI Liquidtight Flexible Nonmetallic Conduit, Type LFNC-A, 6500 Series, Liquidtight Flexible Nonmetallic Conduit. Flame Retardant Three Part PVC Construction. Color: Orange, 1 Inch Diameter, 100
	Foot Carton
Weight per unit	
Product Category	20120105135049
Features	
Inside Diameter	
Material	PVC
outside diameter	1.400/1.450
Material, Color, and Finish	
Color	Orange
Finish	PVC
Jacket Material	PVC
Dimensions and Weight	
Length	100
Descriptions	
Description	1" LFNC ORANGE SEALTIGHT
extra long description	AFC 6504-30-00 1 UL ORANGE LFNC-A 1
Features	LIQUID-TUFF™ Type LFNC-A is a layered Liquidtight Flexible
	Nonmetallic Conduit, designed for use in wet, dry or oily
	locations as a flame resistant, Nonmetallic raceway for power,
	control and communications cables where repetitive motion and
	constant flexing is required. It is intended for applications where
	abrasion and physical abuse may occur. LIQUID-TUFF™ Type
Long Description	LFNC-A carries the UL Listing Marks for US and Canada UL Liquidtight Flexible Nonmetallic Conduit, Type LFNC-A, 6500
Long Description	Series, Liquidtight Flexible Nonmetallic Conduit. Flame Retardant
	Three Part PVC Construction. Color: Orange, 1 inch Diameter, 100
	Foot Carton
Product Type	1 UI Orange LFNC-A 100 CTN
Short Description	1 UL ORANGE LFNC-A 100 CTN
Special Features	Nylon reinforced braid between two layers of PVC for strength
	and flexibility. Sunlight resistant, oil resistant, mild acid
	resistance, non-conductive raceway.



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Flexible Conduit
GTIN	00077680175830
Manufacturers Part Number	6504-30-00
UPC	077680175830
Taxonomies, Classifications, and Cate	egories
Category Description	Liquid Tight
Туре	Liquidtight Flexible Non-Metallic Conduit
Trade Size	
Trade Size	1
Packaging	
Carton	1
Weight	0.29
Weight Per each	0.29
Uses, Certifications, and Standards	
Application	Constant flexing and motion applications
standard	UL 1660 E123464
Temperature Rating	176