



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1011 First Place Blvd
73099-0000, OK Yukon
Phone: 405-265-8424
Fax: 405-494-4041



65216 Led DBL Head Security Flood White No MS

Satco

Catalog Number	65216
Manufacturer	Satco
Description	Led Security Light - Dual Head White Finish 4000K
Weight per unit	2.5 (lbs/each)
Product Category	Security Lights

Features

amperage rating	0.200 to 0.072
Ballast Type	Self
Lamp Type	LED
Material	Die Cast Aluminum
Number of Lamps	2
Power Rating	0.9
Reflector Type	Frost
Socket Type	Integrated
Voltage Rating	120 to 277
Warranty	5 Year Limited - Fixtures
Wattage	20

Material, Color, and Finish

fixture material	die-cast aluminum
Style	Utility

Dimensions and Weight

Height	7.63
Length	7.63
Size	L:7.63 W:4.16 H:4.13
Width	4.16

Descriptions

Description	LED DBL HEAD SECURITY FLOOD WHITE NO MS
extra long description	SATCO 65/216 LED DUAL HEAD SECURITY
Long Description	LED Security Light - Dual Head White Finish 4000K
Product Type	Led Dual Head Security Light
Special Features	Warranty: 5-Years ; FCC Compliant: True ; Cct Selectable: False ; CCT (Kelvin Temp): 4000K ; Hours Rated: 50000 ; Beam Angle (degree): 50 ; Indoor Outdoor: Outdoor ; IP Rating: IP65 ; Lens Finish: Frost ; Lens Material: Glass ; Operating Temp: -30C (-22F) to +50C (+122F) ; Watts: 20W ; Lumens: 1900L



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1011 First Place Blvd
73099-0000, OK Yukon
Phone: 405-265-8424
Fax: 405-494-4041

Manufacturer Information

Brand	Nuvo
GTIN	00045923680403
Manufacturers Part Number	65/216
UPC	045923680403

Taxonomies, Classifications, and Categories

Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE LIGHTING
Type	Commercial LED

Packaging

Carton	1
Weight	2.54
Weight Per each	2.54

Uses, Certifications, and Standards

Application	Outdoor
environmental conditions	Wet
Frequency Rating	50/60
Operating Temperature standard	-30C (-22F) to a maximum of +50C (+122F) cULus - Certified