


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





660RTQ 1/2" Emt Push-In Raintight Coupling *Crouse-Hinds*

Catalog Number	660RTQ
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Push-In Raintight Coupling, Emt, Zinc Die Cast, Raintight, No Disassembly, 1/2"
Weight per unit	0.1400 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Push In
dimensions	1.3500 IN X 1.2600 IN X 1.3500 IN
Insulation Class	NON INSULATED
Material	Zinc Die Cast

Material, Color, and Finish

Color	Gray	
Finish	Zinc	

Dimensions and Weight

	•			
Size		1/2 in		

Description 1/2" EMT PUSH-IN RAINTIGHT COUPLING

Descriptions

extra long description	CRS-H 660RTQ 1/2 EMT PUSH IN CPL RA
Features	Fast installation with no disassembly required! Crouse-Hind series push-in raintight EMT connectors and couplings simply push onto the EMT conduit without the use of any tools or additional labor. Used in raintight environments to join EMT conduit to a box or enclosure, or to couple two ends of EMT conduit. The design prevents water seepage into the conduit, box or enclosure.
Long Description	Eaton Crouse-Hinds series push-in raintight coupling, EMT, Zinc die cast, Raintight, no disassembly, 1/2"
Product Type	1/2 Emt Push In CPL Raintight
Special Features	PUSH IN EMT RAINTIGHT COUPLING

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00662276526075
Manufacturers Part Number	660RTQ
UPC	662276526075



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
	STEEL EMT FITTINGS
Туре	Push-in raintight coupling
Packaging	
Carton	1
Weight Per each	0.14
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
Mounting	Push In
standard	cULus