

MATERIAL SAFETY DATA SHEET

MSDS 0215

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

		HMIS CODES	
PRODUCT NAME		Health	:
Metacaulk Fire Rated Putty Pad/		Flammability	(
Fire Rated Putty Stick		Reactivity	(
PRODUCT CODES		PPI	1
66335, 66340, 66345			
CHEMICAL FAMILY:			
Organic/Inorganic			
USE			
Firestopping Sealant			
MANUFACTURER'S NAME		EMERGENCY TELEPHONE NO.	
The RectorSeal Corporation		Chemtrec 24 Hours	
2601 Spenwick Drive		(800) 424-9300	
Houston, Texas 77055 USA			
DATE OF PREPARATION		TECHNICAL SERVICE TELEPHONE NO.	
July 24, 2002		(800) 231-3345	

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS
--	41583-09-9	Triazine Triamine Phosphate	
		ACGIH TLV	N/D ppm
		OSHA PEL	N/D ppm
--	12007-56-6	Calcium Borate	
		ACGIH TLV	N/D ppm
		OSHA PEL	N/D ppm
--	68333-79-9	Polyphosphoric Acid	
		ACGIH TLV	N/D ppm
		OSHA PEL	N/D ppm
--	29761-21-5	Isodecyldiphenyl Ester	
		ACGIH TLV	N/D ppm
		OSHA PEL	N/D ppm

Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS

    May cause skin irritation.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

    Not a respiratory irritant.

EYE CONTACT

    Contact may cause eye irritation.

SKIN CONTACT

    Contact may cause skin irritation.

INGESTION

    Possible irritation to mucous membranes of the mouth, throat, and stomach

SUMMARY OF CHRONIC HAZARDS

    None known

None known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Persons with pre-existing skin conditions or chemical allergies may be more susceptible to contact effects of product.

=====  
Section 4 -- FIRST AID MEASURES  
-----

If INHALED: Not a respiratory irritant.  
If on SKIN: Wash with soap and water. If irritation occurs, seek medical attention.  
If in EYES: Immediately flush with large amounts of water. If irritation occurs, seek medical attention.  
If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

=====  
Section 5 -- FIRE FIGHTING MEASURES  
-----

FLASH POINT	LEL	UEL
None	N/D	N/D

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heat may build up and rupture closed containers.

=====  
Section 6 -- ACCIDENTAL RELEASE MEASURES  
-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up spills prevent footing hazard. Avoid flushing into sewers, drains, waterways or soil. Wear protective clothing during clean up.

=====  
Section 7 -- HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. To prevent freezing and possible rupture of container, do not store below 40 F.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all product precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

=====  
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

RESPIRATORY PROTECTION (SPECIFY TYPE): None required.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: N/A

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====  
Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
-----

BOILING POINT:	N/A
SPECIFIC GRAVITY (H <sub>2</sub> O = 1):	1.48
VAPOR PRESSURE (mm Hg):	N/A
MELTING POINT:	N/



