



Pass and Seymour  
15A 120V/125V Combination Single-Pole Toggle Switch and Single Receptacle, White  
Part No. 691W



Our standard Pass and Seymour combination switches allow you to add lights to any room in your home without having to add or replace wall boxes.

## Features & Benefits

Easily accessible break-off separate or common feed.

Two devices fit into the space of one.

Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

One-piece heat-treated triple-wipe brass power contacts.

Grounding combination devices meet NEC Requirements.

## Specifications

### General Info

|                     |                         |                    |                             |
|---------------------|-------------------------|--------------------|-----------------------------|
| Product Line        | Pass & Seymour          | Color              | White                       |
| Finish              | Satin                   | UPC Number         | 785007691023                |
| Country Of Origin   | Mexico                  | Material           | Thermoplastic               |
| Features            | Combination             | Switch Type        | Toggle                      |
| Number of Switches  | 1                       | Application Sector | Hospitality, Residential    |
| Wall Plate Included | No                      | Standard           | UL 498                      |
| Warranty Type       | 1-Year Limited Warranty | Type               | Combination, Outlet, Switch |

### Dimensions

|                  |         |                  |         |
|------------------|---------|------------------|---------|
| Product Width US | 1.32 in | Product Depth US | 0.94 in |
|------------------|---------|------------------|---------|

---

|                   |         |
|-------------------|---------|
| Product Height US | 4.06 in |
|-------------------|---------|

---

### Listing Agencies / 3rd Party Agencies

---

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140597 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

---

### Technical Information

---

|             |                    |                |    |
|-------------|--------------------|----------------|----|
| Load Rating | 15 A @ 120/125 VAC | Seismic Tested | No |
|-------------|--------------------|----------------|----|

---

|                  |      |                     |           |
|------------------|------|---------------------|-----------|
| Operating Cycles | 3000 | Connection Location | Side Only |
|------------------|------|---------------------|-----------|

---

|                        |                   |                 |   |
|------------------------|-------------------|-----------------|---|
| Terminal Accommodation | #14 AWG - #12 AWG | Number of Gangs | 1 |
|------------------------|-------------------|-----------------|---|

---

|            |              |          |      |
|------------|--------------|----------|------|
| Throw Type | Single Throw | Amperage | 15 A |
|------------|--------------|----------|------|

---

|                 |             |                       |     |
|-----------------|-------------|-----------------------|-----|
| Number of Poles | Single Pole | Requires Neutral Wire | Yes |
|-----------------|-------------|-----------------------|-----|

---

|                |        |               |          |
|----------------|--------|---------------|----------|
| Indoor/Outdoor | Indoor | Mounting Type | Wall Box |
|----------------|--------|---------------|----------|

---

|                |     |                      |                 |
|----------------|-----|----------------------|-----------------|
| Supply Voltage | 120 | Wire Connection Type | Screw Terminals |
|----------------|-----|----------------------|-----------------|

---

|         |                  |           |  |
|---------|------------------|-----------|--|
| Voltage | 120 VAC, 125 VAC | Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |
|---------|------------------|-----------|--|

---

|                          |                       |
|--------------------------|-----------------------|
| Environmental Conditions | Flammability: UL94 V2 |
|--------------------------|-----------------------|

---



Pass and Seymour  
15A 120V/125V Combination Single-Pole Toggle Switch and Single Receptacle, White  
Part No. 691W



Our standard Pass and Seymour combination switches allow you to add lights to any room in your home without having to add or replace wall boxes.

## Features & Benefits

Easily accessible break-off separate or common feed.

Two devices fit into the space of one.

Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

One-piece heat-treated triple-wipe brass power contacts.

Grounding combination devices meet NEC Requirements.

## Specifications

### General Info

|                     |                         |                    |                             |
|---------------------|-------------------------|--------------------|-----------------------------|
| Product Line        | Pass & Seymour          | Color              | White                       |
| Finish              | Satin                   | UPC Number         | 785007691023                |
| Country Of Origin   | Mexico                  | Material           | Thermoplastic               |
| Features            | Combination             | Switch Type        | Toggle                      |
| Number of Switches  | 1                       | Application Sector | Hospitality, Residential    |
| Wall Plate Included | No                      | Standard           | UL 498                      |
| Warranty Type       | 1-Year Limited Warranty | Type               | Combination, Outlet, Switch |

### Dimensions

|                  |         |                  |         |
|------------------|---------|------------------|---------|
| Product Width US | 1.32 in | Product Depth US | 0.94 in |
|------------------|---------|------------------|---------|

---

|                   |         |
|-------------------|---------|
| Product Height US | 4.06 in |
|-------------------|---------|

---

### Listing Agencies / 3rd Party Agencies

---

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140597 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

---

### Technical Information

---

|             |                    |                |    |
|-------------|--------------------|----------------|----|
| Load Rating | 15 A @ 120/125 VAC | Seismic Tested | No |
|-------------|--------------------|----------------|----|

---

|                  |      |                     |           |
|------------------|------|---------------------|-----------|
| Operating Cycles | 3000 | Connection Location | Side Only |
|------------------|------|---------------------|-----------|

---

|                        |                   |                 |   |
|------------------------|-------------------|-----------------|---|
| Terminal Accommodation | #14 AWG - #12 AWG | Number of Gangs | 1 |
|------------------------|-------------------|-----------------|---|

---

|            |              |          |      |
|------------|--------------|----------|------|
| Throw Type | Single Throw | Amperage | 15 A |
|------------|--------------|----------|------|

---

|                 |             |                       |     |
|-----------------|-------------|-----------------------|-----|
| Number of Poles | Single Pole | Requires Neutral Wire | Yes |
|-----------------|-------------|-----------------------|-----|

---

|                |        |               |          |
|----------------|--------|---------------|----------|
| Indoor/Outdoor | Indoor | Mounting Type | Wall Box |
|----------------|--------|---------------|----------|

---

|                |     |                      |                 |
|----------------|-----|----------------------|-----------------|
| Supply Voltage | 120 | Wire Connection Type | Screw Terminals |
|----------------|-----|----------------------|-----------------|

---

|         |                  |           |  |
|---------|------------------|-----------|--|
| Voltage | 120 VAC, 125 VAC | Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |
|---------|------------------|-----------|--|

---

|                          |                       |
|--------------------------|-----------------------|
| Environmental Conditions | Flammability: UL94 V2 |
|--------------------------|-----------------------|

---