



71A8071001D 100W HPS Multi-Tap Bal

Advance By Signify

Catalog Number	71A8071001D
Manufacturer	Advance By Signify
Description	Reliable Performance Vacuum-Pressure Impregnation Is Used to Re-Enforce The Electrical Insulation Of The Ballast, Preclude Moisture, Inhibit Noise, and Dissipate Heat;Pre-Insulated Voltage Leads Reduce The Risk Of Shock and Shrink Installation Time The Basic Ballast Is The Open Core and Coil Which Is Most Often Used As A Component Within A Lighting Luminaire. The Core and Coil Also Forms The Nucleus Of Philips Advance'S Five Other Ballast Configurations. Vacuum-Pressure Impregnated With A Silica-Filled Pol
Weight per unit	6.9 (lbs/each)
Product Category	Hid Ballast Kits

Features

ANSI Code	S54
Ballast Type	CORE AND COIL
Lamp Type	HIGH PRESSURE SODIUM
Number of Lamps	1
Power Factor	0.90
start type	Pulse
Voltage Rating	120/208/240/277
Wattage	100

Dimensions and Weight

Height	13.58
Width	1.1

Descriptions

Description	100W HPS MULTI-TAP BAL
extra long description	ADV 190371 HPS BAL 100W S54 QUAD KI
Long Description	Reliable performance Vacuum-pressure impregnation is used to re-enforce the electrical insulation of the ballast, preclude moisture, inhibit noise, and dissipate heat;Pre-insulated voltage leads reduce the risk of shock and shrink installation time The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations. Vacuum-pressure impregnated with a silica-filled pol
Product Type	HPS Bal 100W S54 Quad Kit
Special Features	Capacitor Type: DRY CAP



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4510 East Hwy 377
76049-0000, TX Granbury
Phone: 817-573-0675
Fax: 817-573-0776

Manufacturer Information

Brand	Signify Electronics
GTIN	00781087807118
Manufacturers Part Number	190371
UPC	781087807118

Taxonomies, Classifications, and Categories

Category Description	HID BALLASTS
----------------------	--------------

Packaging

Carton	1
Weight Per each	6.91

Uses, Certifications, and Standards

Frequency Rating	60
standard	ULR;CSA certificate;RoHS Compliant