




# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1501 North Cypress Street  
72114-0000, AR N. Little Rock  
Phone: 501-945-9398  
Fax: 501-508-2426



## **7694S4 Cold Shrink QT-Iii Termination Kit 7694-S-4** *Minnesota Mining (3M)*

|                  |                                                                                                                                                                                                                                                                                                                                                                        |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | 7694S4                                                                                                                                                                                                                                                                                                                                                                 |
| Manufacturer     | Minnesota Mining (3M)                                                                                                                                                                                                                                                                                                                                                  |
| Description      | 3M™ Cold Shrink QT Iii 7620 S, 7680 S & 7690 S Series Termination Kit Includes Three 1 Piece, 3 Phase, Skirted Terminations. It Ensures A Pliable, Tight Seal For Tape Shield, Wire Shield and Unishield® Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV. |
| Weight per unit  | 4.3 (lbs/each)                                                                                                                                                                                                                                                                                                                                                         |
| Product Category | Splicing & Terminating Kits                                                                                                                                                                                                                                                                                                                                            |

### **Descriptions**

|                        |                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description            | COLD SHRINK QT-III TERMINATION KIT 7694-S-4                                                                                                                                                                                                                                                                                                                            |
| extra long description | 3M 7000006121 3M™ Cold Shrink QT-II                                                                                                                                                                                                                                                                                                                                    |
| Long Description       | 3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV. |
| Product Type           | 3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690                                                                                                                                                                                                                                                                                                           |

### **Manufacturer Information**

|                           |                        |
|---------------------------|------------------------|
| Brand                     | 3M Electrical Products |
| GTIN                      | 00054007422136         |
| Manufacturers Part Number | 7694S4                 |
| UPC                       | 054007422136           |

### **Taxonomies, Classifications, and Categories**

|                      |                  |
|----------------------|------------------|
| Category Description | HEAT/COLD SHRINK |
| Type                 | QT-III           |

### **Packaging**

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Weight Per each | 4.305 |

### **Uses, Certifications, and Standards**

|             |         |
|-------------|---------|
| Application | Outdoor |
| standard    | IEEE    |