

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## 7695S4 Cold Shrink Qtiii Term Kit 7695-S-4, 5-25/28KV Minnesota Minina (3M)

Catalog Number 7695S4 Manufacturer Minnesota Mining (3M)  Description 3M™ Cold Shrink QT IIi 7620 S, 7680 S & 7690 S Series Termination KIt Includes Three 1 Piece, 3 Phase, Skirted Terminations. It Ensures A Pliable, Tight Seal For Tape Shield, Wire Shield and Unishield® Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV.  Weight per unit 6.1 (lbs/each) Product Category Splicing & Terminating Kits  Descriptions Description COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M 700006122 3M™ Cold Shrink QT-III Long Description 3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-III Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application 0utdoor standard IEEE	Minnesota Mining (3M)	
Description  3M™ Cold Shrink QT lii 7620 S, 7680 S & 7690 S Series Termination Kit Includes Three 1 Piece, 3 Phase, Skirted Terminations. It Ensures A Pliable, Tight Seal For Tape Shield, Wire Shield and Unishield® Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV.  Weight per unit 6.1 (lbs/each) Product Category Splicing & Terminating Kits  Descriptions  Description COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-lii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Catalog Number	7695\$4
Termination Kit Includes Three 1 Piece, 3 Phase, Skirted Terminations. It Ensures A Pliable, Tight Seal For Tape Shield, Wire Shield and Unishield® Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV.  Weight per unit 6.1 (lbs/each) Product Category Splicing & Terminating Kits  Description OCOLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M 7000006122 3M™ Cold Shrink QT-II Long Description 3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-III Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Manufacturer	Minnesota Mining (3M)
Terminations. It Ensures A Pliable, Tight Seal For Tape Shield, Wire Shield and Unishield® Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV.  Weight per unit 6.1 (lbs/each) Product Category Splicing & Terminating Kits  Descriptions  Description COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M 7000006122 3M™ Cold Shrink OT-III Long Description 3M™ Cold Shrink OT III 7620 S, 7680 S & 7690 S Series Terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-III Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type 0T-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Description	3M™ Cold Shrink QT lii 7620 S, 7680 S & 7690 S Series
Wire Shield and Unishield® Power Cables. The Conjunction Of High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV.  Weight per unit 6.1 (lbs/each) Product Category 5plicing & Terminating Kits  Descriptions  Description COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M 7000006122 3M™ Cold Shrink QT-III Long Description 14 Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-III Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK 7ype 0T-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application 0utdoor		Termination Kit Includes Three 1 Piece, 3 Phase, Skirted
High Dielectric Constant Material and Silicone Rubber Insulation Allows The Termination to Withstand Voltages Of 5 to 35KV.  Weight per unit 6.1 (lbs/each) Product Category Splicing & Terminating Kits  Descriptions  Description COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M 7000006122 3M ™ Cold Shrink QT-II Long Description 3M Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143 Manufacturers Part Number 769584 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type 07-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor		·
Meight per unit Product Category Product Category Product Category Product Category Product Category  Splicing & Terminating Kits  Descriptions  COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description AM™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV. Product Type  Manufacturer Information Brand GTIN O0054007422143 Manufacturers Part Number UPC 054007422143  Taxonomies, Classifications, and Categories Category Description Type  Carton HEAT/COLD SHRINK Type OT-III  Packaging Carton 1 Weight Per each Application Outdoor		•
Weight per unit       6.1 (lbs/each)         Product Category       Splicing & Terminating Kits         Descriptions         Description       COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV         extra long description       3M 7000006122 3M™ Cold Shrink QT-III         Long Description       3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series         Termination Kit includes three 1 piece, 3 phase, skirted       terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.         Product Type       3M™ Cold Shrink QT-III Termination Kit 7620-S, 7680-S & 7690         Manufacturer Information         Brand       3M         GTIN       00054007422143         Manufacturers Part Number       7695S4         UPC       054007422143         Taxonomies, Classifications, and Categories         Category Description       HEAT/COLD SHRINK         Type       QT-III         Packaging         Carton       1         Weight Per each       6.1         Uses, Certifications, and Standards         Application       Outdoor		
Product Category  Descriptions  Description  Description  COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description  Alm 7000006122 3M™ Cold Shrink QT-II  Long Description  Alm Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type  Manufacturer Information  Brand GTIN 00054007422143  Manufacturers Part Number UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton Weight Per each  Loudon  Uses, Certifications, and Standards Application Outdoor		· · · · · · · · · · · · · · · · · · ·
Descriptions Description COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV extra long description 3M 7000006122 3M™ Cold Shrink QT-II Long Description 3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV. Product Type 3M™ Cold Shrink QT-IIi Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information Brand GTIN 00054007422143 Manufacturers Part Number 17695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton Weight Per each 1 Weight Per each Outdoor	•	
Description extra long description 3M 700006122 3M™ Cold Shrink QT-II Long Description 3M 700006122 3M™ Cold Shrink QT-II Long Description 3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information Brand GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Product Category	Splicing & Terminating Kits
extra long description  Alm M Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type  Almufacturer Information  Brand  GTIN  GTIN  Manufacturers Part Number  UPC  054007422143  Taxonomies, Classifications, and Categories Category Description  HEAT/COLD SHRINK  Type  QT-III  Packaging  Carton  Weight Per each  1  Weight Per each  Outdoor  Outdoor	Descriptions	
Long Description  3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type  3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand GTIN 00054007422143  Manufacturers Part Number 17695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton Weight Per each 1 Weight Per each Cottdoor Outdoor	Description	COLD SHRINK QTIII TERM KIT 7695-S-4, 5-25/28KV
Termination Kit includes three 1 piece, 3 phase, skirted terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 1. Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	extra long description	3M 7000006122 3M™ Cold Shrink QT-II
terminations. It ensures a pliable, tight seal for tape shield, wire shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143 Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Long Description	3M™ Cold Shrink QT III 7620 S, 7680 S & 7690 S Series
shield and UniShield® power cables. The conjunction of high dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-lii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor		·
dielectric constant material and silicone rubber insulation allows the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-lii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor		
the termination to withstand voltages of 5 to 35kV.  Product Type 3M™ Cold Shrink QT-Iii Termination Kit 7620-S, 7680-S & 7690  Manufacturer Information  Brand 3M GTIN 00054007422143  Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor		
Product Type3M™ Cold Shrink QT-lii Termination Kit 7620-S, 7680-S & 7690Manufacturer InformationBrand3MGTIN00054007422143Manufacturers Part Number7695S4UPC054007422143Taxonomies, Classifications, and CategoriesCategory DescriptionHEAT/COLD SHRINKTypeQT-IIIPackagingCarton1Weight Per each6.1Uses, Certifications, and StandardsApplicationOutdoor		
Manufacturer Information  Brand 3M  GTIN 00054007422143  Manufacturers Part Number 7695S4  UPC 054007422143  Taxonomies, Classifications, and Categories  Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	D 1 1 T	
Brand 3M GTIN 00054007422143 Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Product Type	3M™ Cold Shrink Q1-III Termination Kit 7620-S, 7680-S & 7690
GTIN 00054007422143  Manufacturers Part Number 7695S4  UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Manufacturer Information	
Manufacturers Part Number 7695S4 UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Brand	3M
UPC 054007422143  Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	GTIN	00054007422143
Taxonomies, Classifications, and Categories Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Manufacturers Part Number	7695S4
Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	UPC	054007422143
Category Description HEAT/COLD SHRINK Type QT-III  Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Taxonomies, Classifications, and C	ategories
Packaging Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor		•
Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Туре	QT-III
Carton 1 Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor	Packaging	
Weight Per each 6.1  Uses, Certifications, and Standards Application Outdoor		1
Application Outdoor		6.1
Application Outdoor	· ·	S