



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1336 Swisco Road
70665-0000, LA Sulphur
Phone: 337-533-8019
Fax: 337-533-8055



774016 Toggle Switch, Heavy Duty, DPDT, On-Off-On, Screw *Ideal*

| | |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number | 774016 |
| Manufacturer | Ideal |
| Description | Toggle Switch, 2 Poles, 10 A;20 A, 125/227 V Ac, DPDT Contact Configuration, Solid Brass;Nickel-Plated (Bushing) Material, Screw Connection, Hole Mount, Nickel Plated (Bushing), 1.300 In (L) X 0.760 In (W) X 0.800 In (H), +32 °F Operating Temperature, +185 °F Operating Temperature, 0.11 LB |
| Weight per unit | N/A |
| Product Category | Gen Purpose Switches |

Features

| | |
|------------------|-----------------------------------------------------------|
| action | DPDT |
| amperage rating | 20,10 |
| connection | Screw, 6 Terminals |
| Contact Rating | Factory Tested 100000 Cycles To 21 AMP 14.8 VDC DC Rating |
| operating cycles | 100000 |
| Poles | 2 |
| Switch Type | Toggle |

Dimensions and Weight

| | |
|--------|-------|
| Height | 0.800 |
| Width | 0.760 |

Descriptions

| | |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | TOGGLE SWITCH, HEAVY DUTY, DPDT, ON-OFF-ON, SCREW |
| extra long description | IDEAL 774016 SWITCH,HDTGL,DPDT,O-F- |
| Features | Great for power tool and motor control switch applicationsRugged long-wearing solid brass/nickel-plated bushings1/2 in. diameter mounting holeDielectric Strength: 1500VMechanical Life: 100,000 cyclesOperating Temperature: 32°F to 185°F (0°C to 85°C)DC?Rating: Factory tested 100,000 cycles to 21 Amp 14.8 VDC |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------|
| Category Description | TOGGLE SWITCHES |
| Type | Heavy-Duty, On-Off-On |

Packaging

| | |
|-----------------|---|
| Carton | 1 |
| Weight Per each | 0 |

Uses, Certifications, and Standards

| | |
|----------|----------------------|
| Mounting | 1/2 IN Hole Diameter |
| standard | CSA, RU Listed, RoHS |