



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 840B 6" Plastic Bushing

Topaz - Southwire LLC

Catalog Number	840B
Manufacturer	Topaz - Southwire LLC
Description	Rigid Conduit Insulating Bushing, Threaded Female Type; Thermoplastic Material; 1 Inch; Imc/Rigid Conduit Used On; Ul, Csa Approval; 7.5 Inch Diameter; 105 Deg C Temperature Rating; 10 Per Case Standard Package; 6 Inch Trade Size
Weight per unit	0.1600 (lbs/each)
Product Category	Plastic

### Features

Material	Thermoplastic
Throat Type	PLASTIC INSULATED

### Dimensions and Weight

Diameter	7.5 Inch
Height	1 INCH

### Descriptions

Commodity Description	Rigid Conduit Fittings - Plastic
Description	6" PLASTIC BUSHING
extra long description	FEMALE THREADED TYPE; THERMOPLASTIC MATERIAL; 1 INCH; IMC/RIGID CONDUIT USED ON; UL (CANADA AND US) APPROVAL; 7.5 INCH DIAMETER; 105 DEG C TEMPERATURE RATING; 10 PER CASE STANDARD PACKAGE; 6 INCH TRADE SIZE; PLASTIC INSULATED THROAT TYPE; APPLICATION INDOOR, OUTDOOR
Long Description	RIGID CONDUIT INSULATING BUSHING, THREADED FEMALE TYPE; THERMOPLASTIC MATERIAL; 1 INCH; IMC/RIGID CONDUIT USED ON; UL, CSA APPROVAL; 7.5 INCH DIAMETER; 105 DEG C TEMPERATURE RATING; 10 PER CASE STANDARD PACKAGE; 6 INCH TRADE SIZE
Product Type	Rigid Conduit Insulating Bushing

### Manufacturer Information

Brand	Southwire Rough Electrical Com
GTIN	00751338185609
Manufacturers Part Number	840B
UPC	751338185609

### Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	THREADED FEMALE



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Trade Size

Trade Size ..... 6 INCH

## Packaging

Carton ..... 1

Standard Package ..... 10 PER CASE

Weight Per each ..... 0.16

## Uses, Certifications, and Standards

Approval ..... UL, CSA

Temperature Rating ..... 105 DEG C

Used On ..... IMC/RIGID CONDUIT