



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 8720 2-1/2" Rigid Threadless Coupling

*Abb Installation Products, Inc*

|                  |   |
|------------------|---|
| Catalog Number   | 8720  |
| Manufacturer     | Abb Installation Products, Inc  |
| Description      | 2-1/2 Inch Coupling, Malleable Iron For Use With Threadless Rigid/Imc Conduit |
| Weight per unit  | 5.1 (lbs/each)  |
| Product Category | Rigid Conduit Fittings - Steel  |

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 2-1/2" RIGID THREADLESS COUPLING  |
| extra long description | ABB 8720 2 1/2 IN THREADLESS COUPLI   |
| Long Description       | 2-1/2 Inch Coupling, Malleable Iron for Use with Threadless Rigid/IMC Conduit |
| Product Type           | 2 1/2 In Threadless Coupling  |
| Special Features       | Eliminate Conduit Threading   |

### Manufacturer Information

|                           |                 |
|---------------------------|-----------------|
| Brand                     | T&B Ind Fitting |
| GTIN                      | 00786210087207  |
| Manufacturers Part Number | 8720            |
| UPC                       | 786210087207    |

### Taxonomies, Classifications, and Categories

|                      |  |
|----------------------|--|
| Category Description | Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR |
| Type                 | Compression Couplings & Connectors   |

### Trade Size

|            |          |
|------------|----------|
| Trade Size | 2-1/2 IN |
|------------|----------|

### Packaging

|                 |      |
|-----------------|------|
| Carton          | 5    |
| Weight Per each | 5.06 |

### Uses, Certifications, and Standards

|             |  |
|-------------|--|
| Application | To Couple and Effectively Bond Threaded Ends of Rigid Metal Conduit/Intermediate Conduit Where Neither Length of Conduit Can Be Roated |
| standard    | UL E23018, CSA   |