

## OTHER PRODUCTS

### RectorSeal® Duct Seal

Gray putty compound

| Code  | Description | Qty. |
|-------|-------------|------|
| 81880 | 1 lb.       | 10   |
| 81881 | 5 lbs.      | 2    |



#### FEATURES

- Asbestos free
- Air / water tight seal
- Resistant to water, alcohols, mild acids & bases
- Non-corrosive / non-irritant
- Paintable

**Application** • Permanently soft, non-toxic, putty-type compound which adheres to most clean, dry surfaces

- Can be hand applied from 25°F to 120°F

#### Recommended for

- Sealing around the ends of electrical conduits and boxes
- Flashings
- Service mast entries



### Dark Cutting Oil

Low rpm machine thread cutting oil

| Code  | Description | Qty. |
|-------|-------------|------|
| 94392 | 1 qt.       | 12   |
| 94272 | 1 gal.      | 6    |
| 94192 | 5 gal.      | 1    |
| 94111 | 55 gal.     | 1    |

#### FEATURES

- Increased lubricity/longer die life
- Penetrates quickly
- Keeps dies cool

**Application** • Designed to reduce friction

- Effective coolant and anti-weld agent
- An extreme pressure lubricant during thread cutting operations
- Will not congeal above 20°F



### Copper-Rich™

High temperature anti-seize and lubricant

| Code  | Description | Qty. |
|-------|-------------|------|
| 72851 | 8 oz.       | 12   |
| 72841 | 1 lb.       | 12   |

#### FEATURES

- Highly conductive
- Exceeds military spec MIL-A-907E

**Application** • Pure micro-sized copper flakes dispersed in a non-melt, high temperature grease

- Resists seizure
- Color: copper

#### Recommended for

- All metal connections including stainless steel to 1800°F
- Ideal for use where electrical conductivity is important



## OTHER PRODUCTS

### RectorSeal® Duct Seal

Gray putty compound

| Code  | Description | Qty. |
|-------|-------------|------|
| 81880 | 1 lb.       | 10   |
| 81881 | 5 lbs.      | 2    |



#### FEATURES

- Asbestos free
- Air / water tight seal
- Resistant to water, alcohols, mild acids & bases
- Non-corrosive / non-irritant
- Paintable

**Application** • Permanently soft, non-toxic, putty-type compound which adheres to most clean, dry surfaces

- Can be hand applied from 25°F to 120°F

#### Recommended for

- Sealing around the ends of electrical conduits and boxes
- Flashings
- Service mast entries



### Dark Cutting Oil

Low rpm machine thread cutting oil

| Code  | Description | Qty. |
|-------|-------------|------|
| 94392 | 1 qt.       | 12   |
| 94272 | 1 gal.      | 6    |
| 94192 | 5 gal.      | 1    |
| 94111 | 55 gal.     | 1    |

#### FEATURES

- Increased lubricity/longer die life
- Penetrates quickly
- Keeps dies cool

**Application** • Designed to reduce friction

- Effective coolant and anti-weld agent
- An extreme pressure lubricant during thread cutting operations
- Will not congeal above 20°F



### Copper-Rich™

High temperature anti-seize and lubricant

| Code  | Description | Qty. |
|-------|-------------|------|
| 72851 | 8 oz.       | 12   |
| 72841 | 1 lb.       | 12   |

#### FEATURES

- Highly conductive
- Exceeds military spec MIL-A-907E

**Application** • Pure micro-sized copper flakes dispersed in a non-melt, high temperature grease

- Resists seizure
- Color: copper

#### Recommended for

- All metal connections including stainless steel to 1800°F
- Ideal for use where electrical conductivity is important

