



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



A515M 15 Min Twist Timer Ivory

Nsi Industries

| | |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number | A515M |
| Manufacturer | Nsi Industries |
| Description | The Tork A515M 15-Minute Spring-Wound In-Wall Twist Timer Is Designed to Control A Variety Of Indoor Appliances and Lights. Automate Your Home or Office to Save Energy and Money Using The Simple Twist Knob and Reliable Mechanical Timekeeping. Fits Into A Standard Electrical Box For In-Wall Mounting. Designed For Indoor Loads Such As Lights, Whole House Fans, Air Compressors, Water Heaters or Motors. |
| Weight per unit | 0.4000 (lbs/each) |
| Product Category | Electromechanical Time Switches |

Features

| | |
|----------------|-----------------|
| action | SPDT |
| Base | Wall Plate |
| Contact Rating | 125-250-277 VAC |
| Phase | Single Phase |
| Poles | 1 |
| Timing Range | 15 Minute |

Dimensions and Weight

| | |
|------|-----------------|
| Size | H=5.00 - W=3.00 |
|------|-----------------|



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Descriptions

| | |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | 15 MIN TWIST TIMER IVORY |
| extra long description | TORK A515M Interval Timer 15 Min Wh |
| Features | The TORK A515M spring-wound in-wall twist timer carries our legacy of innovation and quality with reliable timekeeping and consistent performance. Use twist timers to set a countdown for automatically shutting off appliances or lighting, saving you energy and trouble. No more forgetting to turn off a garage light or attic fan: with a twist timer, simply wind the knob to the correct duration and automate the process. TORK twist timers are at home in residential environments or a range of commercial applicat |
| Long Description | The TORK A515M 15-Minute Spring-Wound In-Wall Twist Timer is designed to control a variety of indoor appliances and lights. Automate your home or office to save energy and money using the simple twist knob and reliable mechanical timekeeping. Fits into a standard electrical box for in-wall mounting. Designed for indoor loads such as lights, whole house fans, air compressors, water heaters or motors. |
| Product Type | Interval Timer 15 Min White |
| Special Features | Ivory 15 Minute No Hold In Wall Time Switch |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00786261150134 |
| Manufacturers Part Number | A515M |
| UPC | 786261150134 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------------------|
| Category Description | TIME CLOCKS |
| Type | Spring Wound In Wall Time Switch |

Packaging

| | |
|-----------------|-----|
| Carton | 1 |
| Weight Per each | 0.4 |

Uses, Certifications, and Standards

| | |
|--------------------------|------------------------|
| Application | NSI |
| Enclosure | Single Gang Wall Plate |
| environmental conditions | 32-122 F |
| Frequency Rating | 50-60 Hz |
| Mounting | Single Gang Wall Plate |
| Operating Temperature | 32-122 F |
| standard | cULus |