

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AF26300014 24.2A, 250-500V, 3P Contactor Industrial Connections &

| Catalog Number | AF26300014 |
|------------------|--------------------------------------------------------------|
| Manufacturer | Industrial Connections & |
| Description | 3 Pole, 45 Amp, Non-Reversing Across The Line Contactor With |
| | 250-500V Ac/DC Coil and No Auxiliary Contacts |
| Weight per unit | 830.0 (lbs/each) |
| Product Category | IEC Contactors |

Dimensions and Weight

45x86x86mm Size

Descriptions

| • | |
|------------------------|------------------------------------------------------------------------------------------------------------|
| Description | 24.2A, 250-500V, 3P CONTACTOR |
| extra long description | ABB AF26-30-00-14 CTR,3P,24.2A,250- |
| Long Description | 3 pole, 45 amp, non-reversing across the line contactor with 250-500V AC/DC coil and no auxiliary contacts |
| Product Type | Contacteur 3 Pole 20HP 600vca |
| Special Features | Terminal type: Screw terminals |

Manufacturer Information

| Brand | ABB | |
|---------------------------|----------------|--|
| GTIN | 00804325538732 | |
| Manufacturers Part Number | AF26-30-00-14 | |
| UPC | 804325538732 | |

Taxonomies, Classifications, and Categories

| Category Description | IEC/FREEDOM CONTACTOR |
|----------------------|-----------------------|
| Туре | Contactors |

Packaging

| ckaging | |
|-----------------|-----|
| Carton | 1 |
| Weight Per each | 830 |

Uses, Certifications, and Standards

| Application | Primarily for controlling single and three phase motors and | |
|-----------------------|-------------------------------------------------------------|--|
| | switching power circuits | |
| Operating Temperature | -60 to +80 Degrees C | |
| standard | CB, CCC, cUL, CE, DNV, EAC, RINA, RoHS | |